

## Preface

This manual describes how to install and use the 72128A and 72129A Hardened Managed Ethernet Switch. This switch introduced here is designed to deliver full scalability with SNMP/RMON web-based management functions by providing:

<b>72128A-XT</b>	<b>12-port 10/100Base-TX + 1-port Gigabit Hardened Managed Ethernet Switch</b>
<b>72129A-XT</b>	<b>12-port 10/100Base-TX + 2-port Gigabit Hardened Managed Ethernet Switch</b>
<b>72129A-ZYT</b>	<b>12-port 10/100Base-TX + 2-port Gigabit Hardened Managed Ethernet Switch</b>

Gigabit Options:

**X** = 1 : 1000Base-SX (SC)

2 : 10/100/1000Base-TX

**YY** = DA : Combination of 1-port 10/100/1000Base-TX and 1-port 1000Base-SX (SC)

Power Type:

**T** = Terminal Block power input

To get the most out of this manual, you should have an understanding of Ethernet networking concepts.

In this manual, you will find:

Features on the 72128A and 72129A Hardened Managed Ethernet Switch

- Illustrative LED functions
- Installation instructions
- Management Configuration
- SNMP, DHCP, IGMP...
- Specifications


# Table of Contents

<b>PREFACE</b>	<b>1</b>
<b>TABLE OF CONTENTS</b>	<b>2</b>
<b>PRODUCT OVERVIEW</b>	<b>4</b>
MANAGED ETHERNET SWITCH	4
PACKAGE CONTENTS	4
PRODUCT HIGHLIGHTS	5
<i>Basic Features</i>	5
<i>Management Support</i>	5
FRONT PANEL DISPLAY	7
PHYSICAL PORTS	8
SWITCH MANAGEMENT	9
<i>Web-based browser interface</i>	9
<i>Administration console via RS-232 serial port (CLI)</i>	9
<i>External SNMP-based network management application</i>	9
<b>INSTALLATION</b>	<b>10</b>
SELECTING A SITE FOR THE SWITCH	10
CONNECTING TO POWER	10
<i>DC Terminal Block power input</i>	10
CONNECTING TO YOUR NETWORK	11
<i>Cable Type &amp; Length</i>	11
<i>Cabling</i>	12
<b>SWITCH MANAGEMENT</b>	<b>13</b>
MANAGEMENT ACCESS OVERVIEW	13
ADMINISTRATION CONSOLE (CLI)	14
<i>Direct Access</i>	14
<i>Modem Access</i>	15
WEB MANAGEMENT	15
SNMP-BASED NETWORK MANAGEMENT	15
PROTOCOLS	16
MANAGEMENT ARCHITECTURE	16
<b>WEB-BASED BROWSER MANAGEMENT</b>	<b>17</b>
<b>SNMP &amp; RMON MANAGEMENT</b>	<b>18</b>
OVERVIEW	18
SNMP AGENT AND MIB-2 (RFC 1213)	18
RMON MIB (RFC 1757) AND BRIDGE MIB (RFC 1493)	19
<i>RMON Groups Supported</i>	19
<i>Bridge Groups Supported</i>	20

<b>WEB-BASED BROWSER MANAGEMENT</b>	<b>21</b>
LOGGING ON TO THE SWITCH	21
UNDERSTANDING THE BROWSER INTERFACE	23
SYSTEM	25
PORT	34
SWITCHING	39
TRUNKING	42
STP	43
VLAN	45
QoS	51
SNMP	54
OTHER PROTOCOLS	59
<b>COMMAND LINE CONSOLE MANAGEMENT</b>	<b>62</b>
ADMINISTRATION CONSOLE	62
<i>Exec Mode (View Mode)</i>	63
<i>Privileged Exec Mode (Enable Mode)</i>	67
<i>Configure Mode (Configure Terminal Mode)</i>	71
SYSTEM	75
PORT	82
SWITCHING	86
TRUNKING	91
STP	92
VLAN	99
QoS	105
SNMP	108
OTHER PROTOCOLS	116
<b>SPECIFICATIONS</b>	<b>124</b>
<b>APPENDIX</b>	<b>126</b>

## Product Overview

### Managed Ethernet Switch



---

Front View

### Package Contents

When you unpack the product package, you shall find the items listed below. Please inspect the contents, and report any apparent damage or missing items immediately to your authorized reseller.

- The Managed Ethernet Switch
- User's Manual
- RS232 cable
- Panel-mount brackets with screws



## Product Highlights

### Basic Features

- Complies with NEMA TS1 & TS2 Environmental requirements for Traffic control equipment
- Complies with EN61000-6-2 EMC Generic standard immunity for Industrial environment
- Supports 8192 MAC addresses
- Provides 256K Bytes memory buffer
- Auto-negotiation for speed and duplexity on all TX ports
- Auto-MDIX on all TX ports
- Full wire-speed forwarding rate
- Store-and-forward mechanism
- Half-duplex back-pressure and IEEE802.3x full-duplex compliant flow control
- Power input: 24VDC (Terminal Block)
- -40°C to 75°C (-40°F to 167°F) operating temperature range  
Tested for functional operation @ -40°C to 85°C (-40°F to 185°F)
- Front panel reset button
- Front panel port status LEDs
- Hardened aluminum case
- Supports DIN-Rail, Panel, Rack Mounting installation

### Management Support

#### VLAN

- Port-based VLAN
- IEEE802.1Q tagged VLAN

#### TRUNKING

- MAC-based Trunking with automatic link fail-over

#### PORT-SECURITY

- Per-port programmable MAC address locking
- Up to 24 Static Secure MAC addresses per port

#### PORT-MIRRORING

- Port-mirroring

#### QOS (IEEE802.1p Quality of Service)

- 4 priority queues

#### INTERNETWORKING PROTOCOLS

- Bridging:


IEEE802.1w Rapid Spanning Tree  
IEEE802.1D Spanning Tree compatible  
IEEE802.1Q – GVRP

- IP Multicast:
  - IGMP Snooping
- Rate Control

#### **NETWORK MANAGEMENT METHODS**

- Console port access via RS-232 cable (CLI, Command Line Interface)
- Telnet remote access
- SNMP agent:
  - MIB-2 (RFC1213)
  - Bridge MIB (RFC1493)
  - RMON MIB (RFC1757) – statistics, history, alarm and events
  - VLAN MIB (IEEE802.1Q/RFC2674)
  - Private MIB
- Web browser
- TFTP software-upgrade capability

## Front Panel Display



### ①POWER

This LED comes on when the switch is properly connected to power and turned on.

### ②Port Status LEDs

The LEDs are located at the left side of the front panel, displaying status for each respective port. Please refer to the following table for more details.

LED	State	Indication
<b>10/100TX</b>		
<b>Link/ACT</b>	On	A valid network connection established
	Flashing	Transmitting or receiving data ACT stands for ACTIVITY
<b>10/100</b>	On	Communication speed is 100Mbps
	Off	Communication speed is 10Mbps

LED	State	Indication
<b>10/100/1000TX, 1000SX</b>		
<b>LNK/ACT</b>	On	A valid network connection established
	Flashing	Transmitting or receiving data ACT stands for ACTIVITY
<b>1000</b>	On	Communication speed is 1000Mbps
	Off	Communication speed is 10/100Mbps

## Physical Ports

The Managed Ethernet Switch provides:

<b>72128A-XT</b>	<b>12-port 10/100Base-TX + 1-port Gigabit Hardened Managed Ethernet Switch</b>
<b>72129A-XT</b>	<b>12-port 10/100Base-TX + 2-port Gigabit Hardened Managed Ethernet Switch</b>
<b>72129A-ZYYT</b>	<b>12-port 10/100Base-TX + 2-port Gigabit Hardened Managed Ethernet Switch</b>

Gigabit Options:

**X** = 1 : 1000Base-SX (SC)

2 : 10/100/1000Base-TX

**YY** = DA : Combination of 1-port 10/100/1000Base-TX and 1-port 1000Base-SX (SC)

Power Type:

**T** = Terminal Block power input

### CONNECTIVITY

- SC connectors on 1000SX ports
- RJ-45 connectors on TX ports

### MODE SELECTION

- 10BaseT full-duplex mode
- 10BaseT half-duplex mode
- 100BaseTX full-duplex mode
- 100BaseTX half-duplex mode
- 1000BaseT/SX full-duplex mode
- Auto-negotiating mode

## Switch Management

### Web-based browser interface

The switch also boasts a point-and-click browser-based interface that lets user access full switch configuration and functionality from a Netscape or Internet Explorer browser.

### Administration console via RS-232 serial port (CLI)

The switch provides an onboard serial port, which allows the switch to be configured via a directly connected terminal.

### External SNMP-based network management application

The switch can also be configured via SNMP.

## Installation

This chapter gives step-by-step instructions about how to install the switch:

### Selecting a Site for the Switch

As with any electric device, you should place the switch where it will not be subjected to extreme temperatures, humidity, or electromagnetic interference. Specifically, the site you select should meet the following requirements:

- The ambient temperature should be between  $-40^{\circ}\text{C}$  to  $75^{\circ}\text{C}$  ( $-40^{\circ}\text{F}$  to  $167^{\circ}\text{F}$ ).
- The relative humidity should be less than 95 percent, non-condensing.
- Surrounding electrical devices should not exceed the electromagnetic field (RFC) standards.
- Make sure that the switch receives adequate ventilation. Do not block the ventilation holes on each side of the switch.

### Connecting to Power

#### DC Terminal Block power input

- Step 1:** Connect the supplied DC power cord to the terminal block on the back of the switch, and then plug it into a standard DC outlet with a voltage 24 VDC. Turn on the DC power supply.
- Step 2:** Turn off the DC power supply if you want to shut down the switch.



Rear view

## Connecting to Your Network

### Cable Type & Length

It is necessary to follow the cable specifications below when connecting the switch to your network. Use appropriate cables that meet your speed and cabling requirements.

Cable Specifications

Speed	Connector	Port Speed Half/Full Duplex	Cable	Max. Distance
10BaseT	RJ-45	10/20 Mbps	2-pair UTP/STP Cat. 3, 4, 5	100 m
100BaseTX	RJ-45	100/200 Mbps	2-pair UTP/STP Cat. 5	100 m
1000BaseT	RJ-45	2000 Mbps	4-pair UTP/STP Cat. 5	100 m
1000BaseSX (*Wavelength of 850nm)	SC	2000 Mbps	50 or 62.5/125µm multi-mode fiber	550 m

## **Cabling**

**Step 1:** First, ensure the power of the switch and end devices are turned off.

**<Note>** Always ensure that the power is off before any installation.

**Step 2:** Prepare cable with corresponding connectors for each type of port in use.

**Step 3:** Consult Cable Specifications Table on previous page for cabling requirements based on connectors and speed.

**Step 4:** Connect one end of the cable to the switch and the other end to a desired device.

**Step 5:** Once the connections between two end devices are made successfully, turn on the power and the switch is operational.



## Switch Management

This chapter explains the methods that you can use to configure management access to the switch. It describes the types of management applications and the communication and management protocols that deliver data between your management device (workstation or personal computer) and the system. It also contains information about port connection options.

This chapter covers the following topics:

- Management Access Overview
- Key Concepts
- Key Guidelines for Implementation
- Web Management Access
- Administration Console Access
- SNMP Access
- Standards, Protocols, and Related Reading

### Management Access Overview

The switch gives you the flexibility to access and manage the switch using any or all of the following methods.

The web browser interface and administration console (CLI) support are embedded in the switch software and are available for immediate use.

## Administration Console (CLI)

The administration console is an internal, character-oriented, Command Line Interface (CLI) for performing system administration such as displaying statistics or changing option settings.

Using this method, you can view the administration console from a terminal, personal computer, Apple Macintosh, or workstation connected to the switch's console port.

There are two ways to use this management method: direct access or modem access. The following sections describe these methods.

### Direct Access

Direct access to the administration console is achieved by directly connecting a terminal or a PC equipped with a terminal-emulation program (such as HyperTerminal) to the switch console port.

When using the management method, configure the terminal-emulation program to use the following parameters (you can change these settings after login):

#### [DEFAULT PARAMETERS]

- ◆ 115,200bps
- ◆ 8 data bits
- ◆ No parity
- ◆ 1 stop bit

This management method is often preferred because you can remain connected and monitor the system during system reboots. Also, certain error messages are sent to the serial port, regardless of the interface through which the associated action was initiated. A Macintosh or PC attachment can use any terminal-emulation program for connecting to the terminal serial port. A workstation attachment under UNIX can use an emulator such as TIP.

## Modem Access

You can access the switch's administration console from a PC or Macintosh using an external modem attached to the console port. The switch management program provides **Console Port** screen, accessible from the **Basic Management** screen that lets you configure parameters for modem access.

When you have configured the external modem from the administration console, the switch transmits characters that you have entered as output on the modem port. The switch echoes characters that it receives as input on the modem port to the current administration console session. The console appears to be directly connected to the external modem.

## Web Management

The switch provides a browser interface that lets you configure and manage the switch remotely.

After you set up your IP address for the switch, you can access the switch's web interface applications directly in your web browser by entering the IP address of the switch. You can then use your web browser to list and manage switch configuration parameters from one central location, just as if you were directly connected to the switch's console port.

## SNMP-Based Network Management

You can use an external SNMP-based application to configure and manage the switch. This management method requires the SNMP agent on the switch and the SNMP Network Management Station to use the same community string. This management method, in fact, uses two community strings: the get community string and the set community string. If the SNMP Network management station only knows the set community string, it can read and write to the MIBs. However, if it only knows the get community string, it can only read MIBs. **The default get and set community strings for the switch are public.**

## Protocols

The switch supports the following protocols:

### **VIRTUAL TERMINAL PROTOCOLS, SUCH AS TELNET**

A virtual terminal protocol is a software program, such as Telnet, that allows you to establish a management session from a Macintosh, a PC, or a UNIX workstation. Because Telnet runs over TCP/IP, you must have at least one IP address configured on the switch before you can establish access to it with a virtual terminal protocol.

**<Note>** Terminal emulation is different from a virtual terminal protocol in that you must connect a terminal directly to the console port.

### **SIMPLE NETWORK MANAGEMENT PROTOCOL (SNMP)**

SNMP is the standard management protocol for multivendor IP networks. SNMP supports transaction-based queries that allow the protocol to format messages and to transmit information between reporting devices and data-collection programs. SNMP runs on top of the User Datagram Protocol (UDP), offering a connectionless-mode service.

## Management Architecture

All of the management application modules use the same Messaging Application Programming Interface (MAPI). By unifying management methods with a single MAPI, configuration parameters set using one method (e.g. console port) are immediately displayed the other management methods (e.g. SNMP agent of web browser).

The management architecture of the switch adheres to the IEEE open standard. This compliance assures customers that the switch is compatible with, and will interoperate with other solutions that adhere to the same open standard.

## **Web-Based Browser Management**

The switch provides a web-based browser interface for configuring and managing the switch. This interface allows you to access the switch using a preferred web browser.

This chapter describes how to configure the switch using its web-based browser interface.

## SNMP & RMON Management

This chapter describes the switch's Simple Network Management Protocol (SNMP) and Remote Monitoring (RMON) capabilities.

### Overview

RMON is an abbreviation for the Remote Monitoring MIB (Management Information Base). RMON is a system defined by the Internet Engineering Task Force (IETF) document RFC 1757, which defines how networks can be monitored remotely.

RMONs typically consist of two components: an RMON probe and a management workstation:

- The RMON probe is an intelligent device or software agent that continually collects statistics about a LAN segment or VLAN. The RMON probe transfers the collected data to a management workstation on request or when a pre-defined threshold is reached.
- The management workstation collects the statistics that the RMON probe gathers. The workstation can reside on the same network as the probe, or it can have an in-band or out-of-band connection to the probe.

The switch provides RMON capabilities that allow network administrators to set parameters and view statistical counters defined in MIB-II, Bridge MIB, and RMON MIB. RMON activities are performed at a Network Management Station running an SNMP network management application with graphical user interface.

### SNMP Agent and MIB-2 (RFC 1213)

The SNMP Agent running on the switch manager CPU is responsible for:

- Retrieving MIB counters from various layers of software modules according to the SNMP GET/GET NEXT frame messages.
- Setting MIB variables according to the SNMP SET frame message.
- Generating an SNMP TRAP frame message to the Network Management Station if the threshold of a certain MIB counter is reached or if other trap conditions (such as the following) are met:

**WARM START**

**COLD START**

**LINK UP**

**LINK DOWN**

**AUTHENTICATION FAILURE**

**RISING ALARM**

**FALLING ALARM**

**TOPOLOGY ALARM**

MIB-II defines a set of managed objects in various layers of the TCP/IP protocol suites. MIB-II covers all managed objects from layer 1 to layer 4, and, as a result, is the major SNMP MIB supported by all vendors in the networking industry. The switch supports a complete implementation of SNMP Agent and MIB-II.

## **RMON MIB (RFC 1757) and Bridge MIB (RFC 1493)**

The switch provides hardware-based RMON counters in the switch chipset. The switch manager CPU polls these counters periodically to collect the statistics in a format that complies with the RMON MIB definition.

### **RMON Groups Supported**

The switch supports the following RMON MIB groups defined in RFC 1757:

- RMON Statistics Group – maintains utilization and error statistics for the switch port being monitored.

- RMON History Group – gathers and stores periodic statistical samples from the previous Statistics Group.
- RMON Alarm Group – allows a network administrator to define alarm thresholds for any MIB variable. An alarm can be associated with Low Threshold, High Threshold, or both. A trigger can trigger an alarm when the value of a specific MIB variable exceeds a threshold, falls below a threshold, or exceeds or falls below a threshold.
- RMON Event Group – allows a network administrator to define actions based on alarms. SNMP Traps are generated when RMON Alarms are triggered. The action taken in the Network Management Station depends on the specific network management application.

### **Bridge Groups Supported**

The switch supports the following four groups of Bridge MIB (RFC 1493):

- The dot1dBase Group – a mandatory group that contains the objects applicable to all types of bridges.
- The dot1dStp Group – contains objects that denote the bridge's state with respect to the Spanning Tree Protocol. If a node does not implement the Spanning Tree Protocol, this group will not be implemented. This group is applicable to any transparent only, source route, or SRT bridge that implements the Spanning Tree Protocol.
- The dot1dTp Group – contains objects that describe the entity's transparent bridging status. This group is applicable to transparent operation only and SRT bridges.
- The dot1dStatic Group – contains objects that describe the entity's destination-address filtering status. This group is applicable to any type of bridge which performs destination-address filtering.




## Web-Based Browser Management

The switch provides a web-based browser interface for configuring and managing the switch. This interface allows you to access the switch using a preferred web browser.

This chapter describes how to configure the switch using its web-based browser interface.

### Logging on to the switch



#### SWITCH IP ADDRESS

In your web browser, specify the IP address of the switch. Default IP address is 169.254.1.1.

#### LOGIN

Enter the factory default login ID: root.

## **PASSWORD**


Enter the factory default password (no password).

Or enter a user-defined password if you followed the instructions later and changed the factory default password.

Then click on the “Login” button to log on to the switch.

## Understanding the Browser Interface

The web browser interface provides eight groups of point-and-click buttons at the left field of the screen for configuring and managing the switch.



### SYSTEM

System Information, System Name/Password, IP Address, Save Configuration, Firmware Upgrade, Reboot, Logout

### PORT

Configuration, Port Status, Rate Control, RMON Statistics, Per Port Vlan Activities

### SWITCHING

Bridging, Static MAC Entry, Port Mirroring

### TRUNKING

Port Trunking

### STP

Global Configuration, RSTP Port Setting

**VLAN**

VLAN Mode Setting, 802.1Q VLAN Setting, 802.1Q Port Setting, Port Based VLAN

**QOS**

Global Configuration, 802.1p priority, DSCP

**SNMP**

SNMP General Setting, SNMP v1/v2c, SNMP v3

**OTHER PROTOCOLS**

GVRP, IGMP Snooping


# System

Welcome to Switch Management - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Reload Home Search Favorites Print Mail New Window

Address http://169.254.1.1/cgi-bin/switch.cgi Go Links



Management Switch


- System
  - System Information
  - System Name/Password
  - IP Address
  - Save Configuration
  - Firmware Upgrade
  - Reboot
  - Logout
- Port
- Switching
- Trunking
- STP
- VLAN
- QoS
- SNMP
- Other Protocols

System information

System name	switch_a	
Firmware version	1.42.1 01/06/09 22:00:31	
MAC address	00e0.b391.a000	
Default gateway	None	


VLAN ID	IP Address	IP Subnet Mask
1	169.254.1.1	255.255.0.0

Done Internet




### System Name/Password

1. System Name: Click in "System Name" text box. Type a system name if it is blank, or replace the current system name with a new one.
2. Password: Click in "Password" text box. Type a password.
3. Retype Password: Click in "Retype Password" text box. Type the same password in "Password" text box again to verify it.
4. Updating setting: Click "Updating setting" button to update your settings.



### IP Address


1. IP Address: Click in "IP Address" text box and type a new address to change the IP Address.
2. IP Subnet Mask: Click in "IP Subnet Mask" text box and type a new address to change the IP Subnet Mask.
3. Submit: Click "Submit" button when you finished these selections.
4. You need to enter the new IP address on the browser and reconnect to the switch after IP or subnet mask are changed.
5. Default Gateway: Click "Default Gateway" drop-down menu to choose "Disable" or "Enable" from the "Default Gateway" drop-down list to disable or enable Default Gateway Setting for the switch.  
Click the text box and type a new address to change the Default Gateway. (Need to choose "Enable" from the "Default Gateway" drop-down menu.)
6. Submit: Click "Submit" button when you finished Default Gateway.



### Save Configuration


1. Load config from TFTP server:  
Click in "TFTP Server" text box and type the TFTP server IP address from where the file will be obtained.  
Click in "FILE" text box and type the name of the file that will be obtained.  
Click "Load" button to load the file from the TFTP server.
2. Backup config to TFTP server:  
Click in "TFTP Server" text box and type the TFTP server IP address to where the file will be back upped.  
Click in "FILE" text box and type the name of the file that will be back upped.  
Click "Backup" button to backup the file to the TFTP server.
3. Save Configuration: Click "Save Configuration" button to save your configuration settings.
4. Restore Default: Click "Restore Default" button to restore the default settings of the switch.
5. Auto save: Click "Auto save" drop-down menu to choose "Disable" or "Enable" from the "Auto save" drop-down list to disable or enable Auto save for the switch.
6. Auto save interval (5~65536 sec): Click in "Auto save interval" text box and type a decimal number between 5 and 65536.
7. Submit: Click "Submit" button when you finished Auto save configuration.







### **Firmware Upgrade**

1. **Filename:** Click in "Filename" text box and type the name of the file that you intend to upgrade it to the switch.
2. **TFTP server IP:** Click in "TFTP server IP" text box and type the TFTP server IP address from where the file will be obtained.
3. **Upgrade:** Click "upgrade" button to upgrade firmware to the switch. Please flow the message on the screen during the firmware upgrade process. Do not turn off the power or perform other functions during this period of time. Reboot the switch after completing the upgrade process.





Please follow the message on the screen during the firmware upgrade process. Do not turn off the power or perform other functions during this period of time.




Firmware has been upgraded successfully to the switch. Reboot the switch

after completing the upgrade process.



**Reboot**

Reboot: Click “Reboot” button to restart the switch.

**Logout**

Logout: Click “Logout” button to logout of the switch.

## Port

Port	Link Status	Admin Setting	Speed	Flow control
1	running	Link up	Auto	Enable
2	down	Link up	Auto	Enable
3	down	Link up	Auto	Enable
4	down	Link up	Auto	Enable
5	down	Link up	Auto	Enable
6	down	Link up	Auto	Enable
7	down	Link up	Auto	Enable
8	down	Link up	Auto	Enable
9	down	Link up	Auto	Enable
10	down	Link up	Auto	Enable
11	down	Link up	Auto	Enable
12	down	Link up	Auto	Enable
13	down	Link up	Auto	Enable
14	down	Link up	Auto	Enable

### Configuration

1. Admin Setting: Click "Admin Setting" drop-down menu to choose "Link down" or "Link up" from the "Admin Setting" drop-down list to disable or enable Admin Setting for the port.
2. Speed: Click "Speed" drop-down menu to change the line speed and duplex settings from the "Speed" drop-down list for the port.
3. Flow control: Click "Flow control" drop-down menu to choose "Disable" or "Enable" from the "Flow control" drop-down list to disable or enable Flow control for the port.
4. Submit: Click "Submit" button when you finished configurations.


Management Switch

- System
- Port
  - Configuration
  - Port Status
  - Rate Control
  - RMON Statistics
  - Per Port Vlan Activities
- Switching
- Trunking
- STP
- VLAN
- QoS
- SNMP
- Other Protocols

Port	Link Status	Speed	Duplex	Flow control
1	running	100M	Full	Enable
2	down	10M	Half	Enable
3	down	10M	Half	Enable
4	down	10M	Half	Enable
5	down	10M	Half	Enable
6	down	10M	Half	Enable
7	down	10M	Half	Enable
8	down	10M	Half	Enable
9	down	10M	Half	Enable
10	down	10M	Half	Enable
11	down	10M	Half	Enable
12	down	10M	Half	Enable
13	down	1G	Full	Enable
14	down	1G	Full	Enable

### Port Status

View the Link Status, Speed, Duplex, and Flow control status for all ports.



### Rate Control

1. Ingress: Click in "Ingress" text box and type a new Rate to change the Ingress Rate Control for the port.  
Rate Values: 64kbps, 128kbps, 192kbps, ... , 1.792mbps; 2mbps, 3mbps, 4mbps, ... , 100mbps; 104mbps, 112mbps, 120mbps, ... , 1000mbps.
2. Egress: Click in "Egress" text box and type a new Rate to change the Egress Rate Control for the port.  
Rate Values: 64kbps, 128kbps, 192kbps, ... , 1.792mbps; 2mbps, 3mbps, 4mbps, ... , 100mbps; 104mbps, 112mbps, 120mbps, ... , 1000mbps.
3. Update setting: Click "Update setting" button when you finished these Rate Control settings.



Management Switch

- System
- Port
  - Configuration
  - Port Status
  - Rate Control
  - RMON Statistics
  - Per Port Vlan Activities
- Switching
- Trunking
- STP
- VLAN
- QoS
- SNMP
- Other Protocols

Port1	Port2	Port3	Port4	Port5	Port6	Port7
Port8	Port9	Port10	Port11	Port12	Port13	Port14

**Port 1 Statistics**

Drop Events	0
Broadcast Packets Received	146
Multicast Packets Received	6
Undersize Packets Received	0
Oversize Packets Received	0
fragments_pkts	0
64-byte Packets Received	16002
65 to 127-byte Packets Received	5347
128 to 255-byte Packets Received	24
256 to 511-byte Packets Received	5230
512 to 1023-byte Packets Received	10
1.0 to 1.5-kbyte Packets Received	0
Jabber Packets	0
Bytes Received	3344050
Packets Received	26613
Collisions	0
CRC/Alignment Errors Received	0
TX No Errors	23960
RX No Errors	26613

## RMON Statistics

Click Port 1 ~ Port 14 to view corresponding RMON Statistics.

**Welcome to Switch Management - Microsoft Internet Explorer**

Address: <http://169.254.1.1/cgi-bin/switch.cgi>

**Port Links:**

<a href="#">Port1</a>	<a href="#">Port2</a>	<a href="#">Port3</a>	<a href="#">Port4</a>	<a href="#">Port5</a>	<a href="#">Port6</a>	<a href="#">Port7</a>
<a href="#">Port8</a>	<a href="#">Port9</a>	<a href="#">Port10</a>	<a href="#">Port11</a>	<a href="#">Port12</a>	<a href="#">Port13</a>	<a href="#">Port14</a>


**P1 status**

Total VLAN Count	1
Total MAC Address Count	1
VLAN Membership	MAC Address
VLAN1	00e0.b310.aaa9

### Per port vlan activities


Click Port 1 ~ Port 14 to view corresponding vlan activities.

# Switching



## Bridging

1. Aging Time (seconds): Click the text box and type a decimal number as Bridging Aging Time in seconds.
2. Update setting: Click "update setting" button when you finished Aging Time settings.
3. Threshold level (0-100): Click in "Level" text box and type a decimal number for the port. Need to choose "Broadcast" and/or "DLF-Multicast" from "Storm-control enabled type" for the port. DLF (Destination Lookup Failure).
4. Storm-control enabled type: Choose "Broadcast" and/or "DLF-Multicast" from "Storm-control enabled type" for the port.
5. Update Setting: Click "Update Setting" button when you finished Threshold level and Storm-control enabled type settings.




## Static MAC Entry

1. Add MAC address: Click in "Add MAC address" text box and type a locked forwarding MAC address for the port.
2. Delete MAC address: Click "Delete MAC address" drop-down menu and choose a locked forwarding MAC address from the "Delete MAC address" drop-down list to be deleted from the port.
3. Submit: Click "Submit" button when you finished Add MAC address and Delete MAC address settings.

## Static-MAC-Entry Discard:

1. Add MAC address: Click in "Add MAC address" text box and type a MAC address to be discarded for the port.
2. VLAN ID: Click "VLAN ID" drop-down menu and choose a VLAN ID from the "VLAN ID" drop-down list.
3. Delete MAC address: Click "Delete MAC address" drop-down menu and choose a MAC address from the "Delete MAC address" drop-down list to be discarded from the port.


- Submit: Click “Submit” button when you finished Static-MAC-Entry Discard settings.



### Port Mirroring

- Mirror From: Choose Mirror From port from Port 1 ~ Port 14.
- Mirror To: Click “Mirror To” drop-down menu to Choose Mirror To port (Port 1 ~ Port 14) from “Mirror To” drop-down list.
- Mirror Mode: Click “Mirror Mode” drop-down menu to Choose “Tx/Rx”, “Tx”, or “Rx” from “Mirror Mode” drop-down list.
- Submit: Click “Submit” button when you finished Port Mirroring settings.

# Trunking



## Port Trunking

### Static Channel Group:

1. Trunk 1: Click Port 1 ~ Port 12 to assign ports to Trunk 1. (Maximum 4 ports in Trunk 1.)

### GE Trunking:

1. Trunk 3: Click "Static" or "Disable" for Trunk 3. (Trunk 3 includes Port 13 and Port 14.)
2. Submit: Click "Submit" button when you finished Port Trunking settings.

## STP

**Welcome to Switch Management - Microsoft Internet Explorer**

File Edit View Favorites Tools Help

Back Forward Stop Search Favorites Go Links

Address <http://169.254.1.1/cgi-bin/switch.cgi>

**Management Switch**

- System
- Port
- Switching
- Trunking
- STP
  - [Global Configuration](#)
  - [RSTP Port Setting](#)
- VLAN
- QoS
- SNMP
- Other Protocols

Status	
Bridge ID	800000e0b391a001
Designated Root	800000e0b391a001
Reg Root ID	
Root Port	0
Root Path Cost	0
Current Max Age (sec)	20
Current Hello Time (sec)	2
Current Forward Delay (sec)	15
Hold Time (sec)	
Topology Change Count	
Time Since Last Topology Change	

Setting	
Spanning Tree Protocol	Enable
Bridge Priority (0..61440)	32768
Hello Time (sec)	2
Max Age (sec)	20
Forward Delay (sec)	15
STP Version	RSTP

Update setting

**Global Configuration**

1. Spanning Tree Protocol: Click "Spanning Tree Protocol" drop-down menu to Choose "Enable" or "Disable" from "Spanning Tree Protocol" drop-down list to enable or disable Spanning Tree Protocol.
2. Bridge Priority (0..61440): Click in "Bridge Priority" text box and type a decimal number between 0 and 61440.
3. Hello Time (sec) (1..9): Click in "Hello Time" text box and type a decimal number between 1 and 9.
4. Max Age (sec) (6..28): Click in "Max Age" text box and type a decimal number between 6 and 28.
5. Forward Delay (sec) (4..30): Click in "Forward Delay" text box and type a decimal number between 4 and 30.
6. STP Version: Click "STP Version" drop-down menu to choose "RSTP" or "STP compatible" from "STP Version" drop-down list.
7. Update setting: Click "Update setting" button when you finished Global Configuration.

Management Switch

- System
- Port
- Switching
- Trunking
- STP
  - Global Configuration
  - RSTP Port Setting**
- VLAN
- QoS
- SNMP
- Other Protocols

Port	Port Status	Priority	Path Cost	Point to Point Link	Edge Port
1	Designated(Forwarding)	128	200000	point-to-point	Disabled
2	Disabled(Discarding)	128	2000000	shared	Disabled
3	Disabled(Discarding)	128	2000000	shared	Disabled
4	Disabled(Discarding)	128	2000000	shared	Disabled
5	Disabled(Discarding)	128	2000000	shared	Disabled
6	Disabled(Discarding)	128	2000000	shared	Disabled
7	Disabled(Discarding)	128	2000000	shared	Disabled
8	Disabled(Discarding)	128	2000000	shared	Disabled
9	Disabled(Discarding)	128	2000000	shared	Disabled
10	Disabled(Discarding)	128	2000000	shared	Disabled
11	Disabled(Discarding)	128	2000000	shared	Disabled
12	Disabled(Discarding)	128	2000000	shared	Disabled
13	Disabled(Discarding)	128	20000	shared	Disabled
14	Disabled(Discarding)	128	20000	shared	Disabled

RSTP Port Configuration

Port	Priority(Granularity 16)	Admin. Path Cost	Point to Point Link	Edge Port
1	128	200000	Enable	Disable


Update Setting

### RSTP Port Setting

1. STP Version: Click "STP Version" drop-down menu to choose "RSTP" from "STP Version" drop-down list.
2. Port: Click "Port" drop-down menu to Choose Port 1 ~ Port 14 from "Port" drop-down list.
3. Priority(Granularity 16): Click in "Priority" text box and enter a value between 0 and 240 to set the priority for the port. A higher priority will designate the port to forward packets first. A lower number denotes a higher priority. This entry must be divisible by 16. The default priority setting is 128.
4. Admin. Path Cost: Click in "Admin. Path Cost" text box and enter a value between 0 and 2000000 to set the Admin. Path Cost for the port. 0 (auto) - Setting 0 for the Admin. Path Cost will automatically set the speed for forwarding packets to the port for optimal efficiency. Default port cost: 100Mbps port = 200000. Gigabit port = 20000.
5. Point to Point Link: Click "Point to Point Link" drop-down menu to Choose "Enable" or "Disable" from "Point to Point Link" drop-down list to enable or disable Point to Point Link for the port.
6. Edge Port: Click "Edge Port" drop-down menu to Choose "Enable", "Disable", or "Auto" from "Edge Port" drop-down list to set Enable, Disable, or Auto Edge Port for the port.
7. Update setting: Click "Update setting" button when you finished RSTP Port Setting.





# VLAN



## **VLAN Mode Setting**

1. VLAN Mode Setting: Click “VLAN Mode Setting” drop-down menu to Choose “Tag-based VLAN” or “Port-based VLAN” from “VLAN Mode Setting” drop-down list.
2. Update Setting: Click “Update Setting” button when you finished VLAN Mode Setting.




### **802.1Q VLAN Setting**

Add VLAN:

1. VLAN setting: Click “VLAN setting”. The “VLAN Setting” window appears.
2. Add VLAN: Click “Add VLAN” button to create a new VLAN from “VLAN Setting” window.
3. VLAN ID(2-4094): Click in the “VLAN ID” textbox and specify a new VLAN ID number from 2 ~ 4094.
4. VLAN Name: Click in the “VLAN Name” textbox and type a name for this newly created VLAN.


Add port to or delete port from VLAN:

1. VLAN Member: Choose the port to be added to or deleted from the VLAN.
2. Tag or Untag: Click “Tag or Untag” drop-down menu to Choose “Tag” or “Untag” from “Tag or Untag” drop-down list for a “Hybrid” port.
3. Submit: Click “Submit” button when you finished VLAN setting.





Delete VLAN:

1. VLAN setting: Click “VLAN setting”. The “VLAN Setting” window appears.
2. Delete VLAN: Click “Delete VLAN” button.
3. Select a VLAN ID: Click “Select a VLAN ID” drop-down menu from “Select a VLAN ID” drop-down list to choose the VLAN to be deleted.
4. Submit: Click “Submit” button when you finished VLAN setting.



## 802.1Q Port Setting

1. VLAN Port Setting: Click "VLAN Port Setting". The "VLAN Port Setting" window appears.
2. Mode: Click "Mode" drop-down menu to Choose "Access", "Trunk", or "Hybrid" from "Mode" drop-down list for the port. The port will be Tag port if you choose "Trunk" Mode for the port. And the port will be Tag or Untag port if you choose "Hybrid" Mode for the port.
3. PVID: Click in the "PVID" textbox and specify a new PVID number for the port.
4. Update Setting: Click "Update Setting" button when you finished VLAN Port Setting.




## Port Based VLAN

1. VLAN: Choose the port to be added to or deleted from the VLAN.


2. Select all: Click “select all” button to choose Port 1 ~ Port 14 all to be added to the VLAN.
3. Delete all: Click “delete all” button to choose Port 1 ~ Port 14 all to be deleted from the VLAN.
4. Submit: Click “Submit” button when you finished Port Based VLAN setting.

# QoS



## Global Configuration

1. QoS: Click "QoS" drop-down menu from "QoS" drop-down list to choose "Enable" or "Disable" to enable or disable QoS.
2. Trust: Enable or disable the switch port to trust the CoS (Class of Service) labels of all traffic received on that port. Enable or disable a routed port to trust the DSCP (Differentiated Service Code Point) labels of all traffic received on that port.
3. Policy: Choose "Strict Priority(Queue3) + WRR(Queue0-2)" or "WRR(Queue0-3)". A strict priority queue is always emptied first. The queues that are used in the WRR (Weighted Round Robin) are emptied in a round-robin fashion, and you can configure the weight for each queue.
4. Weighted Round Robin: Click in the "Weight(1~55)" textbox and specify a new number from 1 ~ 55 for Queue 0 ~ 3.
5. Submit: Click "Submit" button when you finished Global Configuration.



### 802.1p Priority

1. Priority: Click "Priority" drop-down menu from "Priority" drop-down list to choose 0 ~ 3 for VLAN Priority 0 ~ 7.
2. Submit: Click "Submit" button when you finished 802.1p priority.




Welcome to Switch Management - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Reload Home Search Favorites Print Mail News RSS Feeds

Address http://169.254.1.1/cgi-bin/switch.cgi Go Links



Management Switch

- System
- Port
- Switching
- Trunking
- STP
- VLAN
- QoS
  - Global Configuration
  - DSCP
- SNMP
- Other Protocols

DSCP	Priority	DSCP	Priority	DSCP	Priority	DSCP	Priority
0	0	1	0	2	0	3	0
4	0	5	0	6	0	7	0
8	0	9	0	10	0	11	0
12	0	13	0	14	0	15	0
16	0	17	0	18	0	19	0
20	0	21	0	22	0	23	0
24	0	25	0	26	0	27	0
28	0	29	0	30	0	31	0
32	0	33	0	34	0	35	0
36	0	37	0	38	0	39	0
40	0	41	0	42	0	43	0
44	0	45	0	46	0	47	0
48	0	49	0	50	0	51	0
52	0	53	0	54	0	55	0
56	0	57	0	58	0	59	0
60	0	61	0	62	0	63	0


Submit

Done Internet

## DSCP

1. Priority: Click "Priority" drop-down menu from "Priority" drop-down list to choose 0 ~ 3 for DSCP Priority 0 ~ 3.
2. Submit: Click "Submit" button when you finished DSCP.

# SNMP




## SNMP General Setting

1. **SNMP Status:** Click “SNMP Status” drop-down menu from “SNMP Status” drop-down list to choose “Enable” or “Disable” to enable or disable SNMP.
2. **Description:** Click in the “Description” textbox and specify a new description for SNMP.
3. **Location:** Click in the “Location” textbox and specify a new location for SNMP.
4. **Contact:** Click in the “Contact” textbox and specify a new contact for



## SNMP.

5. Trap Community Name: For each "Trap Community Name", Click in the "Trap Community Name" textbox and specify a trap community name.
6. Trap Host IP Address: For each "Trap Host IP Address", Click in the "Trap Host IP Address" textbox and specify a trap host IP address.
7. Cold Start Trap: Click "Cold Start Trap" drop-down menu from "Cold Start Trap" drop-down list to choose "Enable" or "Disable" to enable or disable cold start trap.
8. Warm Start Trap: Click "Warm Start Trap" drop-down menu from "Warm Start Trap" drop-down list to choose "Enable" or "Disable" to enable or disable warm start trap.
9. Link Down Trap: Click "Link Down Trap" drop-down menu from "Link Down Trap" drop-down list to choose "Enable" or "Disable" to enable or disable link down trap.
10. Link Up Trap: Click "Link Up Trap" drop-down menu from "Link Up Trap" drop-down list to choose "Enable" or "Disable" to enable or disable link up trap.
11. Authentication Failure Trap: Click "Authentication Failure Trap" drop-down menu from "Authentication Failure Trap" drop-down list to choose "Enable" or "Disable" to enable or disable authentication failure trap.
12. Topology Change Trap: Click "Topology Change Trap" drop-down menu from "Topology Change Trap" drop-down list to choose "Enable" or "Disable" to enable or disable topology change trap.
13. Update Setting: Click "Update Setting" button when you finished SNMP General Setting.

**SNMP v1/v2c**


1. Get Community Name: Click in the "Get Community Name" textbox and

- specify a get community name.
2. Set Community Name: Click in the “Set Community Name” textbox and specify a set community name.
3. Update Setting: Click “Update Setting” button when you finished SNMP V1/V2c Setting.



**SNMP v3****Add User:**


1. Add User: Click “Add User” button. The “SNMP V3 Setting” window appears.
2. SNMP Version: Click “SNMP Version” drop-down menu from “SNMP Version” drop-down list to choose “SNMPv3 No-Auth”, “SNMPv3 Auth-MD5”, “SNMPv3 Auth-SHA”, “SNMPv3 Priv Auth-MD5”, or “SNMPv3 Priv Auth-SHA”.
  - SNMPv3 No-Auth: Add a user using SNMP v3 without authentication.
  - SNMPv3 Auth-MD5: Add a user using SNMP v3 with authentication. Click in the “Auth. Password” textbox and specify an authentication password.
  - SNMPv3 Auth-SHA: Add a user using SNMP v3 with authentication. Click in the “Auth. Password” textbox and specify an authentication password.
  - SNMPv3 Priv Auth-MD5: Add a user using SNMP v3 with authentication and privacy. Click in the “Auth. Password” textbox and specify an authentication password. Click in the “Privacy PassPhrase” textbox and specify a privacy pass phrase.
  - SNMPv3 Priv Auth-SHA: Add a user using SNMP v3 with authentication and privacy. Click in the “Auth. Password” textbox and specify an authentication password. Click in the “Privacy PassPhrase” textbox and specify a privacy pass phrase.
3. User Name: Click in the “User Name” textbox and specify a user name for user using SNMP v3.
4. Access Mode: Click “Access Mode” drop-down menu from “Access Mode” drop-down list to choose “Read Only” or “Read/Write”.
  - Read Only: Add a user using SNMP v3 with read-only access mode.
  - Read/Write: Add an user using SNMP v3 with read-write access mode
5. Sumit: Click “Sumit” button when you finished SNMP V3 Setting.



### Delete User:

1. Delete User: Click "Delete User" button. The "Select User Name" window appears.
2. Select User Name: Click "Select User Name" drop-down menu from "Select User Name" drop-down list to choose the user to be deleted from using SNMP v3.
3. Sumit: Click "Sumit" button when you finished user deletion.

## Other Protocols



### GVRP


#### GVRP Global Setting:

1. GVRP: Click “GVRP” drop-down menu from “GVRP” drop-down list to choose “Enable” or “Disable” to enable or disable GVRP (GARP VLAN Registration Protocol).
2. Dynamic VLAN creation: Click “Dynamic VLAN creation” drop-down menu from “Dynamic VLAN creation” drop-down list to choose “Enable” or “Disable” to enable or disable Dynamic VLAN creation. GARP (Generic Attribute Registration Protocol) provides IEEE802.1Q compliant VLAN pruning and dynamic VLAN creation on IEEE802.1Q trunk ports.

3. Update Setting: Click "Update Setting" button when you finished GVRP Global Setting.

Per port setting (include LAG):

1. GVRP: Click "GVRP" drop-down menu from "GVRP" drop-down list to choose "Enable" or "Disable" to enable or disable GVRP for the port.
2. GVRP applicant: Click "GVRP applicant" drop-down menu from "GVRP applicant" drop-down list to choose "Active" or "Normal" to the port. Ports in the GVRP active applicant state send GVRP VLAN declarations when they are in the STP (Spanning Tree Protocol) blocking state, which prevents the STP bridge protocol data units (BPDUs) from being pruned from the other port. Ports in the GVRP normal applicant state do not declare GVRP VLANs when in the STP blocking state.
3. GVRP registration: Click "GVRP registration" drop-down menu from "GVRP registration" drop-down list to choose "Enable" or "Disable" to enable or disable GVRP registration to the port. Configuring an IEEE802.1Q trunk port in registration mode allows dynamic creation (if dynamic VLAN creation is enabled), registration, and deregistration of VLANs on the trunk port.
4. Update Setting: Click "Update Setting" button when you finished Per port setting.



### **IGMP Snooping**

1. IGMP mode: Click "IGMP mode" drop-down menu from "IGMP mode" drop-down list to choose "Disable", "Passive", or "querier" for the switch. Disable: Disable IGMP on the switch. Passive: The switch with only multicast-data-forwarding capability. Querier: The switch acts as the



querier for the network. There is only one querier on a network at any time.

2. Update Setting: Click "Update Setting" button when you finished IGMP mode settings.
3. VLAN ID: Click "VLAN ID" drop-down menu from "VLAN ID" drop-down list to choose the VLAN under configuration for the switch.
4. IGMP version: Click "IGMP version" drop-down menu from "IGMP version" drop-down list to choose "1", "2", or "3" for the switch.
5. Fast-leave: Click "fast-leave" drop-down menu from "fast-leave" drop-down list to choose "Enable" or "Disable" for the switch. Enable this function will allow members of a multicast group to leave the group immediately when an IGMP Leave Report Packet is received by the Switch.

#### IGMP querier:

1. Query-interval: Click in the "query-interval" textbox and specify a new number from 1 ~ 18000. The query-interval field is used to set the time (in seconds) between transmitting IGMP queries. Entries between 1 and 18000 seconds are allowed. Default = 125.
2. Max-response-time: Click in the "max-response-time" textbox and specify a new number from 1 ~ 124. This determines the maximum amount of time in seconds allowed before sending an IGMP response report. The max-response-time field allows an entry between 1 and 124 (seconds). Default = 10.

#### IGMP passive snooping:

1. Report suppression: Click "report suppression" drop-down menu from "report suppression" drop-down list to choose "Enable" or "Disable" for the switch. Use this command to enable report suppression for IGMP version 1 and version 2. Report suppression does not apply to IGMP version 3, and is turned off by default for IGMP versionn1 and IGMP version 2 reports. The switch uses IGMP report suppression to forward only one IGMP report per multicast router query to multicast devices. When IGMP router suppression is enabled, the switch sends the first IGMP report from all hosts for a group to all the multicast routers. The switch does not send the remaining IGMP reports for the group to the multicast routers. This feature prevents duplicate reports from being sent to the multicast devices.
2. Update Setting: Click "Update Setting" button when you finished IGMP Snooping.

## Command Line Console Management

The switch provides a command line console interface for configuration purposes. The switch can be configured either locally through its RS-232 port or remotely via a Telnet session. For the later, you must specify an IP address for the switch first.

This chapter describes how to configure the switch using its console by Command Line.

### Administration Console

Connect the DB9 null-modem or cross over cable to the RS-232 serial port of the device to the RS-232 serial port of the terminal or computer running the terminal emulation application.

Direct access to the administration console is achieved by directly connecting a terminal or a PC equipped with a terminal-emulation program (such as HyperTerminal) to the switch console port.

When using the management method, configure the terminal-emulation program to use the following parameters (you can change these settings after login):

[Default parameters]


115,200bps

8 data bits

No parity

1 stop bit


## Exec Mode (View Mode)



### Logon to Exec Mode (View Mode)

At the **switch\_a login:** prompt just type in “root” and press <Enter> to logon to Exec Mode (or View Mode).

switch\_a login: root



### Basic commands

Exec Mode (or View Mode) is the base mode from where users can perform basic commands like:

clear, debug, disable, enable, exit, help, logout, no, quit, show, terminal

The CLI contains a text-based help facility. Access this help by typing in the full or partial command string then typing a question mark "?". The CLI displays the command keywords or parameters along with a short description.

At the **switch\_a>** prompt just press <?> to list the above basic commands.

```
switch_a>?
```

```
115200 - HyperTerminal
File Edit View Call Transfer Help
switch_a login: root
Switch version 1.30.r142-sdkr32. 12/05/07 13:59:04
switch_a>?
Exec commands:
clear      Clear the Forwarding database
debug      Debugging functions (see also 'undebug')
disable    Turn off privileged mode command
enable     Turn on privileged mode command
exit       End current mode and down to previous mode
help       Description of the interactive help system
logout     Exit from the EXEC
no         Negate a command or set its defaults
quit       Exit current mode and down to previous mode
restore    To restore the default setting
show       Show running system information
terminal   Set terminal line parameters

switch_a>
```

At the **switch\_a>** prompt just type in the full or partial command string then typing a question mark "?" to display the command keywords or parameters along with a short description.

```
switch_a>show ?
```

```

switch_a>show ?
all-if          all-if
brand           Brand ID
bridge         bridge protocol
cli            Show CLI tree of current mode
debugging      Debugging functions (see also 'undebug')
etherchannel    LACP channel commands
flowcontrol     IEEE 802.3x Flow Control
gmrp           Generic Attribute Registration Protocol
gvrp           GARP Vlan Registration Protocol
hardware       Hardware configuration
history        Display the session command history
interface      The layer2 interfaces
ip             Internet Protocol (IP)
lacp           LACP commands
lacp-counter   LACP commands
list           Show command lists
mac            Mac address
mirror         Port Mirroring
mls            Switch(L2).
port           port commands
privilege      Show current privilege level
--More--

```

Connected 0:05:08 VT1003 115200 8-N-1 SCROLL CAPS NUM Capture Print echo

```

gvrp           GARP Vlan Registration Protocol
hardware       Hardware configuration
history        Display the session command history
interface      The layer2 interfaces
ip             Internet Protocol (IP)
lacp           LACP commands
lacp-counter   LACP commands
list           Show command lists
mac            Mac address
mirror         Port Mirroring
mls            Switch(L2).
port           port commands
privilege      Show current privilege level
ratecontrol    The layer2 interface
spanning-tree  Display spanning-tree information
static-channel-group Static channel commands
storm-control  The layer2 interface
user-priority  Display the default user priority associated with the
               layer2 interface
users          Display information about terminal lines
version        Display version
vlan           Display VLAN information

switch_a>show

```

Connected 0:05:59 VT1003 115200 8-N-1 SCROLL CAPS NUM Capture Print echo

### Login timed out


The login session to Exec Mode (or View Mode) has timed out due to an extended period of inactivity (60 seconds) to indicate authentication attempt timed out. And the **switch\_a login:** prompt will show on the screen.

### Logon back to Exec Mode (View Mode)

At the **switch\_a login:** prompt just type in "root" and press <Enter> to logon

back to Exec Mode (or View Mode).

```
switch_a login: root
```




```
115200 - HyperTerminal
File Edit View Call Transfer Help
switch_a login: root
Switch version 1.30.r142-sdkr32. 12/05/07 13:59:04
switch_a>
Vty connection is timed out...
switch_a login:
Login timed out after 60 seconds.
switch_a login:
Connected 0:18:59 VT1003 115200 8-N-1 SCROLL CAPS NUM Capture Print echo
```

### Exit from Exec Mode (View Mode)

At the **switch\_a>** prompt just type in “exit” and press <Enter> to exit from Exec Mode (or View Mode).

```
switch_a>exit
```




```
115200 - HyperTerminal
File Edit View Call Transfer Help
switch_a login: root
Switch version 1.30.r142-sdkr32. 12/05/07 13:59:04
switch_a>exit
switch_a login:
Connected 0:19:58 VT1003 115200 8-N-1 SCROLL CAPS NUM Capture Print echo
```

## Privileged Exec Mode (Enable Mode)

### Logon to Privileged Exec Mode (Enable Mode)

At the **switch\_a>** prompt just type in “enable” and press <Enter> to logon to Privileged Exec Mode (or Enable Mode). And the **switch\_a#** prompt will show on the screen.

```
switch_a>enable
```



### Commands

Privileged Exec Mode (or Enable Mode) allows users to run commands as following.

At the **switch\_a#** prompt just press <?> to list the commands.

```
switch_a#?
```

```

switch_a>enable
switch_a#?
Exec commands:
clear      Clear the Forwarding database
configure  Enter configuration mode
copy       Copy from one file to another
debug      Debugging functions (see also 'undebug')
disable    Turn off privileged mode command
enable     Turn on privileged mode command
exit       End current mode and down to previous mode
help       Description of the interactive help system
install    Install to flash
logout     Exit from the EXEC
no         Negate a command or set its defaults
ping       Send echo messages
quit       Exit current mode and down to previous mode
reload     Reboot the system
restore    To restore the default setting
show       Show running system information
telnet     Open a telnet connection
terminal   Set terminal line parameters
traceroute Trace route to destination
undebug    Disable debugging functions (see also 'debug')
--More--
  
```

```

Exec commands:
clear      Clear the Forwarding database
configure  Enter configuration mode
copy       Copy from one file to another
debug      Debugging functions (see also 'undebug')
disable    Turn off privileged mode command
enable     Turn on privileged mode command
exit       End current mode and down to previous mode
help       Description of the interactive help system
install    Install to flash
logout     Exit from the EXEC
no         Negate a command or set its defaults
ping       Send echo messages
quit       Exit current mode and down to previous mode
reload     Reboot the system
restore    To restore the default setting
show       Show running system information
telnet     Open a telnet connection
terminal   Set terminal line parameters
traceroute Trace route to destination
undebug    Disable debugging functions (see also 'debug')
write      Write

switch_a#_
  
```

At the **switch\_a#** prompt just type in the full or partial command string then typing a question mark “?” to display the command keywords or parameters along with a short description.

switch\_a#show ?



```

switch_a#show ?
all-if          all-if
brand           Brand ID
bridge         bridge protocol
cli            Show CLI tree of current mode
debugging      Debugging functions (see also 'undebug')
etherchannel    LACP channel commands
flowcontrol     IEEE 802.3x Flow Control
gmrp           Generic Attribute Registration Protocol
gvrp           GARP Vlan Registration Protocol
hardware       Hardware configuration
history        Display the session command history
interface      The layer2 interfaces
ip             Internet Protocol (IP)
lACP           LACP commands
lACP-counter   LACP commands
list           Show command lists
mac            Mac address
memory         Memory information
mirror         Port Mirroring
mls            Switch(L2).
nsm            NSM
--More--

```

Connected 0:03:49 VT1003 115200 8-N-1 SCROLL CAPS NUM Capture Print echo

```

ip             Internet Protocol (IP)
lACP           LACP commands
lACP-counter   LACP commands
list           Show command lists
mac            Mac address
memory         Memory information
mirror         Port Mirroring
mls            Switch(L2).
nsm            NSM
port           port commands
privilege      Show current privilege level
ratecontrol    The layer2 interface
running-config Current Operating configuration
spanning-tree  Display spanning-tree information
startup-config Contents of startup configuration
static-channel-group Static channel commands
storm-control  The layer2 interface
user-priority  Display the default user priority associated with the
               layer2 interface
users          Display information about terminal lines
version        Display version
vlan           Display VLAN information

switch_a#show _

```

Connected 0:04:44 VT1003 115200 8-N-1 SCROLL CAPS NUM Capture Print echo

### Login timed out


The login session to Privileged Exec Mode (or Enable Mode) has timed out due to an extended period of inactivity (60 seconds) to indicate authentication attempt timed out. And the **switch\_a login:** prompt will show on the screen.

### Logon back to Exec Mode (View Mode)

At the **switch\_a login:** prompt just type in "root" and press <Enter> to logon

back to Exec Mode (or View Mode).


```
switch_a login: root
```



### Exit from Privileged Exec Mode (or Enable Mode)

At the **switch\_a#** prompt just type in “exit” and press <Enter> to exit from Privileged Exec Mode (or Enable Mode).

```
switch_a#exit
```




## Configure Mode (Configure Terminal Mode)

### Logon to Configure Mode (Configure Terminal Mode)

At the **switch\_a#** prompt just type in “configure terminal” and press <Enter> to logon to Configure Mode (or Configure Terminal Mode). And the **switch\_a(config)#** prompt will show on the screen.

```
switch_a#configure terminal
```





### Commands

Configure Mode (or Configure Terminal Mode) serves as a gateway into the modes as following.

At the **switch\_a(config)#** prompt just press <?> to list the commands.

```
switch_a(config)#?
```



At the **switch\_a(config)#** prompt just type in the full or partial command string then typing a question mark "?" to display the command keywords or parameters along with a short description.

switch\_a(config)#show ?

```

help          Description of the interactive help system
hostname      Set system's network name
interface     Select an interface to configure
ip            Internet Protocol (IP)
lacp          LACP commands
line          Configure a terminal line
log           Logging control
mls           Switch(L2).
no            Negate a command or set its defaults
priority-queue Enable the egress expedite queue
service       Set up miscellaneous service
set           Set GMRP Registration to Fixed Registration
show          Show running system information
snmp-server   Configure snmp setting
username      Establish User Name Authentication
vlan          Configure VLAN parameters
wrr-queue     WRR queue

switch_a(config)#show ?
cli           Show CLI tree of current mode
list          Show command lists
running-config Current Operating configuration

switch_a(config)#show _

```


### Login timed out

The login session to Configure Mode (or Configure Terminal Mode) has timed out due to an extended period of inactivity (60 seconds) to indicate authentication attempt timed out. And the **switch\_a login:** prompt will show on the screen.

### Logon back to Exec Mode (View Mode)

At the **switch\_a login:** prompt just type in "root" and press <Enter> to logon back to Exec Mode (or View Mode).

```
switch_a login: root
```



```
switch_a login: root
Switch version 1.30.r142-sdkr32. 12/05/07 13:59:04
switch_a>enable
switch_a#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
switch_a(config)#
Vty connection is timed out...


switch_a login:
Login timed out after 60 seconds.

switch_a login: root
Switch version 1.30.r142-sdkr32. 12/05/07 13:59:04
switch_a>
```

### Exit from Configure Mode (or Configure Terminal Mode)

At the **switch\_a(config)#** prompt just type in "exit" and press <Enter> to exit from Configure Mode (or Configure Terminal Mode).

```
switch_a(config)#exit
```



```
switch_a login: root
Switch version 1.30.r142-sdkr32. 12/05/07 13:59:04
switch_a>enable
switch_a#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
switch_a(config)#exit
switch_a#_
```

## System

System Information, System Name/Password, IP Address, Save Configuration, Firmware Upgrade, Reboot, Logout.

### System Name/Password

System Name:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **hostname** command to set or change the network server name.

Use the **no hostname** command to disable this function.

3. Command Syntax:

(no) hostname HOSTNAME

HOSTNAME specifies the network name of the system.

4. Example:

The following example sets the hostname to **switch**, and shows the change in the prompt:

```
switch_a(config)#hostname switch
switch(config)#
```

Password:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **enable password** command to modify or create a password to be used when entering the Enable mode.

3. Command Syntax:

enable password PASSWORD

PASSWORD specifies the new password of the system.

4. Example:

The following example sets the new password **mypasswd** to switch:

```
switch_a(config)#enable password mypasswd
switch_a(config)#
```

### IP Address

IP Address/IP Subnet Mask:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **ip address** command to set the IP address of an interface.

Use the **no ip address** command to remove the IP address from an interface.

3. Command Syntax:

ip address IP-ADDRESS

no ip address IP-ADDRESS

no ip address

IP-ADDRESS A.B.C.D/M specifies the IP address and prefix length of an interface.

M specifies IP subnet mask, 8: 255.0.0.0, 16: 255.255.0.0, 24: 255.255.255.0.

4. Example:

The following example sets the new IP address **169.254.1.1** and new IP subnet mask **255.255.0.0** to switch:

```
switch_a(config-if)#ip address 169.254.1.1/16
switch_a(config-if)#
```

Default Gateway:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **ip default-gateway** command to set the IP address of the default gateway.

Use the **no ip default-gateway** command to remove the IP address of the default gateway.

3. Command Syntax:

ip default-gateway IP-ADDRESS

no ip default-gateway

IP-ADDRESS A.B.C.D specifies the IP address of the default gateway.

4. Example:

The following example sets the default gateway **169.254.1.254** to switch:

```
switch_a(config)#ip default-gateway 169.254.1.254
switch_a(config)#
```



### **Save Configuration**

Load config from TFTP server:

1. Command Mode: Privileged Exec mode  
Logon to Privileged Exec Mode (Enable Mode).  
The **switch\_a#** prompt will show on the screen.

```
switch_a#
```

2. Command:

Use **install image** command to load configuration file from tftp server to switch.

3. Command Syntax:

install image IP-ADDRESS WORD

IP-ADDRESS specifies the IP address of tftp server.

WORD specifies the file name to be loaded to switch.

4. Example:

The following example specifies loading configuration file (file name: **WORD**) from tftp server (IP address: **169.254.1.2**) to switch:

```
switch_a#install image 169.254.1.2 WORD
switch_a#
```

Load config to TFTP server:

1. Command Mode: Privileged Exec mode  
Logon to Privileged Exec Mode (Enable Mode).  
The **switch\_a#** prompt will show on the screen.

```
switch_a#
```

2. Command:

Use **write config-file** command to backup configuration file to tftp server.

3. Command Syntax:

write config-file IP-ADDRESS

IP-ADDRESS specifies the IP address of tftp server.

4. Example:

The following example backups configuration file to tftp server (IP address: **169.254.1.2**):

```
switch_a#write config-file 169.254.1.2
switch_a#
```

Save Configuration:

1. Command Mode: Privileged Exec mode  
Logon to Privileged Exec Mode (Enable Mode).  
The **switch\_a#** prompt will show on the screen.

```
switch_a#
```

2. Command:

Use **copy running-config startup-config** command to write configurations

to the file to be used at startup. This is the same as the **write memory** command.

3. Command Syntax:  
copy running-config startup-config

4. Example:

The following example specifies writing configurations to the file to be used at startup to switch:

```
switch_a#copy running-config startup-config
switch_a#
```

Restore Default:

1. Command Mode: Privileged Exec mode  
Logon to Privileged Exec Mode (Enable Mode).  
The **switch\_a#** prompt will show on the screen.

```
switch_a#
```

2. Command:  
Use **restore default** command to restore default setting of the switch.

3. Command Syntax:  
restore default

4. Example:

The following example restores default setting of the switch:

```
switch_a#restore default
switch_a#
```

Auto Save:

1. Command Mode: Configure mode  
Logon to Configure Mode (Configure Terminal Mode).  
The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Usage:

Use this command to enable auto save configuration function. The configuration will be automatically saved at every configured interval while this command is enabled. Use the no form of this command to disable this feature.

3. Command Syntax:  
service auto-config enable  
no service auto-config enable

4. Example:

The following example enables or disables auto save configuration to switch:

```
switch_a(config)#service auto-config enable
switch_a(config)#no service auto-config enable
```

```
switch_a(config)#
```

Auto Save Interval (5~65536 sec):

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Usage:

Use this command to set the interval when the configuration would be automatically saved. The range of interval value is from 5 to 65535. And the default value is 30 seconds.

3. Command Syntax:

service auto-config interval WORD

WORD specifies the interval value.

4. Example:

The following example sets the interval WORD (**10**) when the configuration would be automatically saved to switch:

```
switch_a(config)#service auto-config interval 10
switch_a(config)#
```

### ***Firmware Upgrade***

1. Command Mode: Privileged Exec mode

Logon to Privileged Exec Mode (Enable Mode).

The **switch\_a#** prompt will show on the screen.

```
switch_a#
```

2. Command:

Use **install image** command to upgrade firmware from tftp server to switch.

3. Command Syntax:

install image IP-ADDRESS WORD

IP-ADDRESS specifies the IP address of tftp server.


WORD specifies the file name to be upgraded to switch.

4. Example:

The following example specifies upgrading firmware (file name: **WORD**) from tftp server (IP address: **169.254.1.2**) to switch:

```
switch_a#install image 169.254.1.2 WORD
switch_a#
```

Please follow the message on the screen during the firmware upgrade process. Do not turn off the power or perform other functions during this period of time.




```
115200 - HyperTerminal
File Edit View Call Transfer Help

switch_a login: root

Switch version 1.42.1 01/06/09 22:00:31
switch_a>enable
switch_a#install image 169.254.1.2 flash.tgz
Download now, please wait...
tftp flash.tgz from ip 169.254.1.2 success!!
Install now. This may take several minutes, please wait...
Install success!
switch_a#
```

Connected 0:00:52 VT100 115200 8-N-1 SCROLL CAPS NUM Capture Print echo

At the “switch\_a#” prompt just type in “reload” and press <Enter> to reboot the switch after completing the upgrade process.



```
115200 - HyperTerminal
File Edit View Call Transfer Help

switch_a#reload
Reboot now, please wait...
The system is going down NOW !!
Sending SIGTERM to all processes.

% Connection is closed by administrator!
Sending SIGKILL to all processes.
Requesting system reboot.
Start bootloader ...
Uncompressing image ...
Starting image ...
.....
switch_a login:
```

Connected 1:02:26 VT100 115200 8-N-1 SCROLL CAPS NUM Capture Print echo

**Reboot**

1. Command Mode: Privileged Exec mode  
Logon to Privileged Exec Mode (Enable Mode).  
The **switch\_a#** prompt will show on the screen.

```
switch_a#
```

2. Command:  
Use **reload** command to restart switch.

3. Command Syntax:  
reload

4. Example:  
The following example specifies restarting switch:

```
switch_a#reload  
switch_a login:
```

**Logout**

1. Command Mode: Exec mode or Privileged Exec mode  
Logon to Exec Mode (View Mode) or Privileged Exec Mode (Enable Mode).  
The **switch\_a>** or **switch\_a#** prompt will show on the screen.

```
switch_a>
```

```
switch_a#
```

2. Command:  
Use **logout** command to exit from the Exec mode or Privileged Exec mode.

3. Command Syntax:  
logout

4. Example:  
The following example specifies to exit from the Exec mode or Privileged Exec mode.

```
switch_a>logout  
switch_a login:
```

## Port

Configuration, Port Status, Rate Control, RMON Statistics, Per Port Vlan Activities.

### Configuration

Admin Setting:

1. Command Mode: Interface mode  
Logon to Configure Mode (Configure Terminal Mode).  
Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use the **shutdown** command to shut down the selected interface.  
Use the **no shutdown** to disable this function.

3. Command Syntax:  
(no) shutdown

4. Example:

The following example shows the use of the **shutdown** command to shut down the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#shutdown
switch_a(config-if)#
```

Duplex:

1. Command Mode: Interface mode  
Logon to Configure Mode (Configure Terminal Mode).  
Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **duplex** command to specify the duplex mode to be used for each interface.

Use the **no duplex** to disable this function.

3. Command Syntax:  
(no) duplex MODE

MODE specifies the duplex mode: auto, full, half.

4. Example:

The following example shows the use of **duplex MODE (full)** to the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#duplex full
switch_a(config-if)#
```

Flow control:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **flowcontrol on** command to enable flow control, and configure the flow control mode for the port.

Use the **no flowcontrol** to disable this function.

3. Command Syntax:

```
flowcontrol on
no flowcontrol
```

4. Example:

The following example shows the use of **flowcontrol on** to the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#flowcontrol on
switch_a(config-if)#
```

### **Port Status**

1. Command Mode: Exec mode or Privileged Exec mode

Logon to Exec Mode (View Mode) or Privileged Exec Mode (Enable Mode).

The **switch\_a>** or **switch\_a#** prompt will show on the screen.

```
switch_a>
```

```
switch_a#
```

2. Command:

Use the **show interface** command to display interface configuration and status.

3. Command Syntax:

```
show interface IFNAME
```

IFNAME specifies the name of the interface for which status and configuration information is desired.

### 4. Example:

The following example shows the use of **show interface** to display interface configuration and status of the interface fe1 (port 1):

```
switch_a>show interface fe1
```

### Rate Control

#### 1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

#### 2. Command:

Use this command to specify the ingress/egress rate to be used for each interface. The bandwidth value is in bits.

Use the no parameter with this command to remove the ingress/egress rate to be used for each interface.

#### 3. Command Syntax:

(no) rate-control ingress/egress VALUE

VALUE

<1-100000000000 bits> (usable units: k, m, g)

<1-999>k|m for 1 to 999 kilo bits or mega bits.

1g for 1 giga bits.

### 4. Example:

The following example shows the use of rate-control ingress VALUE (**10 mega bits**) to the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#rate-control ingress 10m
switch_a(config-if)#
```

### RMON Statistics

#### 1. Command Mode: Exec mode or Privileged Exec mode

Logon to Exec Mode (View Mode) or Privileged Exec Mode (Enable Mode).

The **switch\_a>** or **switch\_a#** prompt will show on the screen.

```
switch_a>
```

```
switch_a#
```

#### 2. Command:

Use the **show interface statistics** command to display RMON statistics of interface.

#### 3. Command Syntax:

show interface statistics IFNAME



IFNAME specifies the name of the interface for which RMON statistics is desired.

4. Example:

The following example shows the use of **show interface statistics** to display RMON statistics of the interface fe1 (port 1):

```
switch_a>show interface statistics fe1
```

### **Per Port Vlan Activities**

1. Command Mode: Exec mode or Privileged Exec mode

Logon to Exec Mode (View Mode) or Privileged Exec Mode (Enable Mode).

The **switch\_a>** or **switch\_a#** prompt will show on the screen.

```
switch_a>
```

```
switch_a#
```

2. Command:

Use **show vlan** command to display information about a particular VLAN by specifying the VLAN ID.

3. Command Syntax:

```
show vlan <2-4094>
```

<2-4094> VLAN ID.

4. Example:

The following is an output of **show vlan** command displaying information about VLAN 2:

```
switch_a>show vlan 2
```

## Switching

Bridging, Static MAC Entry, Port Mirroring

### **Bridging**

Aging Time (seconds):

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to specify an ageing-out time for a learned MAC address. The learned MAC address will persist till this specified time.

3. Command Syntax:

Bridge GROUP ageing-time AGEINGTIME

no bridge GROUP ageing-time

Group = <1-1> The ID of the bridge-group that this ageing time is for.

AGEINGTIME = <10-1000000> The number of seconds of persistence.

4. Example:

The following example sets the new AGEINGTIME (**1000**) to bridge GROUP (**1**):

```
switch_a(config)#bridge 1 ageing-time 1000
switch_a(config)#
```

Threshold level (0-100):

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **storm-control level** command to specify the rising threshold level for broadcasting, multicast, or destination lookup failure traffic. The storm control action occurs when traffic utilization reaches this level.

3. Command Syntax:

storm-control level LEVEL

LEVEL <0-100> specifies the percentage of the threshold; percentage of the maximum speed (pps) of the interface.

4. Example:

The following example shows setting **storm-control level LEVEL (30)** to the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#storm-control level 30
switch_a(config-if)#
```

Broadcast:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **storm-control broadcast enable** command to enable broadcast traffic.

Use **no storm-control broadcast** command to disable broadcast traffic.

3. Command Syntax:

storm-control broadcast enable

no storm-control broadcast

4. Example:

The following example shows setting **storm-control broadcast enable** to the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#storm-control broadcast enable
switch_a(config-if)#
```

Multicast:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **storm-control multicast enable** command to enable multicast traffic.

Use **no storm-control multicast** command to disable multicast traffic.

3. Command Syntax:

storm-control multicast enable

no storm-control multicast

4. Example:

The following example shows setting **storm-control multicast enable** to the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#storm-control multicast enable
switch_a(config-if)#
```

DLF:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **storm-control dlf enable** command to enable destination lookup failure traffic.

Use **no storm-control dlf** command to disable destination lookup failure traffic.

3. Command Syntax:

storm-control dlf enable

no storm-control dlf

dlf destination lookup failure

4. Example:

The following example shows setting **storm-control dlf enable** to the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#storm-control dlf enable
switch_a(config-if)#
```

### Static MAC Entry

Add MAC address/Delete MAC address:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to statically configure a bridge entry to forward or discard matching frames.

3. Command Syntax:

bridge GROUP address MAC forward|discard IFNAME

no bridge GROUP address MAC forward|discard IFNAME

GROUP <1-1> Bridge-group ID used for bridging.

MAC the Media Access Control (MAC) address in the HHHH.HHHH.HHHH

format.

IFNAME the interface on which the frame comes in.

4. Example:

The following example configures a bridge GROUP (1) to forward matching frames (MAC address **2222.2222.2222**) to the interface fe1 (port 1):

```
switch_a(config)#bridge 1 address 2222.2222.2222 forward fe1
switch_a(config)#
```

Static-MAC-Entry Discard:

1. Command Mode: Configure mode

Login to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Usage:

Use this command to statically configure a bridge entry to discard matching frames.

3. Command Syntax:

bridge GROUP address MAC discard IFNAME

no bridge GROUP address MAC discard IFNAME

GROUP <1-1> Bridge-group ID used for bridging.

MAC the Media Access Control (MAC) address in the HHHH.HHHH.HHHH format.

IFNAME the interface on which the frame comes in.

4. Example:

The following example configures a bridge GROUP (1) to discard matching frames (MAC address **2222.2222.2222**) to the interface fe1 (port 1):

```
switch_a(config)#bridge 1 address 2222.2222.2222 discard fe1
switch_a(config)#
```

### **Port Mirroring**

1. Command Mode: Interface mode

Login to Configure Mode (Configure Terminal Mode).

Then login to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use this command to define a mirror source port and its direction.

Use the no parameter with this command to disable port mirroring by the destination port on the specified source port.

3. Command Syntax:

mirror interface SOURCEPORT direction SNOOPDIRECTION

no mirror interface SOURCEPORT

SOURCEPORT Name of the Source interface to be used.

SNOOPDIRECTION [both|receive|transmit]

both Specifies mirroring of traffic in both directions.

receive Specifies mirroring of received traffic.

transmit Specifies mirroring of transmitted traffic.

#### 4. Example:

The following example enables port mirroring by the destination port fe1 (port 1) on the specified source port fe2 (port 2):

```
switch_a(config)#interface fe1
switch_a(config-if)#mirror interface fe2 direction both
switch_a(config-if)#
```

## Trunking

### Port Trunking

#### **Port Trunking**

1. Command Mode: Interface mode  
Logon to Configure Mode (Configure Terminal Mode).  
Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Usage:

Use **static-channel-group** command to create a static aggregator, or add a member port to an already-existing static aggregator.

Use the **no static-channel-group** command to detach the port from the static aggregator.

3. Command Syntax:

static-channel-group <1-3>

no static-channel-group

<1-3> Channel group number.

Maximum 4 ports in static-channel-group 1 and static-channel-group 2.

Maximum 2 ports in static-channel-group 3

4. Example:

The following example adding the interface fe1 (port 1) to **static-channel-group 1**:

```
switch_a(config)#interface fe1
switch_a(config-if)#static-channel-group 1
switch_a(config-if)#
```

## STP

### Global Configuration, RSTP Port Setting

#### Global Configuration

STP Version:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to choose the Spanning Tree protocol or Rapid Spanning Tree protocol.

3. Command Syntax:

bridge GROUP protocol PROTOCOL vlan-bridge

GROUP <1-1> Bridge group name used for bridging.

PROTOCOL

ieee IEEE 802.1Q spanning-tree protocol.

rstp IEEE 802.1w rapid spanning-tree protocol.

4. Example:

The following example chooses the PROTOCOL (**rstp**) on bridge GROUP (1):

```
switch_a(config)#bridge 1 protocol rstp vlan-bridge
switch_a(config)#
```

Rapid Spanning Tree Protocol:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to enable the Rapid Spanning Tree protocol on a bridge.

Use the no form of the command to disable the Rapid Spanning Tree protocol on a bridge.

3. Command Syntax:

bridge GROUP rapid-spanning-tree enable

no bridge GROUP rapid-spanning-tree enable BRIDGE-FORWARD

GROUP <1-1> Bridge group name used for bridging.

BRIDGE-FORWARD Puts all ports of the specified bridge into the forwarding state.



4. Example:

The following example enables or disables the **rapid-spanning-tree** on bridge GROUP (1):

```
switch_a(config)#bridge 1 rapid-spanning-tree enable
switch_a(config)#no bridge 1 rapid-spanning-tree enable bridge-forward
switch_a(config)#
```

Spanning Tree Protocol:

1. Command Mode: Configure mode

Login to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to enable the Spanning Tree protocol on a bridge.

Use the no form of the command to disable the Spanning Tree protocol on a bridge.

3. Command Syntax:

bridge GROUP spanning-tree enable

no bridge GROUP spanning-tree enable BRIDGE-FORWARD

GROUP <1-1> Bridge group name used for bridging.

BRIDGE-FORWARD Puts all ports of the specified bridge into the forwarding state.

4. Example:

The following example enables or disables the **spanning-tree** on bridge GROUP (1):

```
switch_a(config)#bridge 1 spanning-tree enable
switch_a(config)#no bridge 1 spanning-tree enable bridge-forward
switch_a(config)#
```

Bridge Priority (0..61440):

1. Command Mode: Configure mode

Login to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to set bridge priority for the common instance. Using a lower priority indicates a greater likelihood of the bridge becoming root.

3. Command Syntax:

bridge GROUP priority PRIORITY

no bridge GROUP priority

GROUP <1-1> The ID of the bridge group for which the priority is set.

PRIORITY <0-61440> The bridge priority.

4. Example:

The following example sets the **priority** PRIORITY (**4096**) of bridge GROUP (1):

```
switch_a(config)#bridge 1 priority 4096
switch_a(config)#
```

Hello Time (sec) (1..9):

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to set the hello-time, the time in seconds after which (if this bridge is the root bridge) all the bridges in a bridged LAN exchange Bridge Protocol Data Units (BPDUs).

3. Command Syntax:

bridge GROUP hello-time HELLOTIME

no bridge GROUP hello-time

GROUP <1-1> The ID of the bridge group to which this hello time is assigned.

HELLOTIME <1-9> The hello BPDU interval in seconds.

4. Example:

The following example sets the **hello-time** HELLOTIME (**9**) of bridge GROUP (1):

```
switch_a(config)#bridge 1 hello-time 9
switch_a(config)#
```

Max Age (sec) (6..28):

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to set the max-age for a bridge.

Use the no parameter with this command to restore the default value of max-age.

3. Command Syntax:

bridge GROUP max-age MAXAGE

no bridge GROUP max-age

GROUP <1-1> The ID of the bridge group to which this maximum age time is assigned.

MAXAGE <6-28> The maximum time, in seconds, to listen for the root bridge.

4. Example:

The following example sets the **max-age** MAXAGE (28) of bridge GROUP (1):

```
switch_a(config)#bridge 1 max-age 28
switch_a(config)#
```

Forward Delay (sec) (4..30):

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to set the time (in seconds) after which (if this bridge is the root bridge) each port changes states to learning and forwarding.

Use the no parameter with this command to restore the default value.

3. Command Syntax:

bridge GROUP forward-time FORWARD\_DELAY

no bridge GROUP forward-time

GROUP <1-1> The ID of the bridge group to which this delay time is assigned.

FORWARD\_DELAY <4-30> the forwarding time delay in seconds.

4. Example:

The following example sets the **forward-time** FORWARD\_DELAY (30) of bridge GROUP (1):

```
switch_a(config)#bridge 1 forward-time 30
switch_a(config)#
```

### **RSTP Port Setting**

Priority(Granularity 16):

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use this command to set the port priority for a bridge. The lower priority indicates a greater likelihood of the bridge becoming root.

3. Command Syntax:

bridge GROUP priority PRIORITY

GROUP <1-1> the ID of the bridge group.

PRIORITY <0-240> The priority to be assigned to the group.

4. Example:

The following example sets the priority **PRIORITY (100)** of the interface fe1 (port 1) of bridge **GROUP (1)**:

```
switch_a(config)#interface fe1
switch_a(config-if)#bridge 1 priority 100
switch_a(config-if)#
```

Admin. Path Cost:

1. Command Mode: Interface mode  
Logon to Configure Mode (Configure Terminal Mode).  
Then logon to Interface mode.  
fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use this command to set the cost of a path associated with a bridge-group.  
Use the no parameter with this command to restore the default cost of a path associated with a bridge-group.

3. Command Syntax:

```
bridge GROUP path-cost PATHCOST
no bridge GROUP path-cost
GROUP <1-1> the ID of the bridge group.
PATHCOST <1-200000000> The cost to be assigned to the group.
```

4. Example:

The following example sets the cost (**123**) of the interface fe1 (port 1) of bridge **GROUP (1)**:

```
switch_a(config)#interface fe1
switch_a(config-if)#bridge 1 path-cost 123
switch_a(config-if)#
```

Point to Point Link:

1. Command Mode: Interface mode  
Logon to Configure Mode (Configure Terminal Mode).  
Then logon to Interface mode.  
fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **spanning-tree link-type** command to set the link type of a port to enable or disable rapid transition.  
Use the **no spanning-tree link-type** command to set a port to its default state and to disable rapid transition.

3. Command Syntax:

(no) spanning-tree link-type LINKTYPE

LINKTYPE The link type to be assigned to the port.

point-to-point Enable rapid transition.

shared Disable rapid transition.

4. Example:

The following example sets the link-type LINKTYPE (**point-to-point**) of the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#spanning-tree link-type point-to-point
switch_a(config-if)#
```

Autoedge:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **spanning-tree autoedge** command to assist in automatic identification of the edge port.

Use the **no spanning-tree autoedge** command to disable this feature.

3. Command Syntax:

(no) spanning-tree autoedge

4. Example:

The following example enables the **spanning-tree autoedge** of the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#spanning-tree autoedge
switch_a(config-if)#
```

Edgeport:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **spanning-tree edgeport** command to set a port as an edge-port and to enable rapid transitions.

Use the **no spanning-tree edgeport** command to set a port to its default

state (not an edge-port) and to disable rapid transitions.

3. Command Syntax:  
(no) spanning-tree edgeport

4. Example:

The following example enables the **spanning-tree edgeport** of the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#spanning-tree edgeport
switch_a(config-if)#
```

## VLAN

VLAN Mode Setting, 802.1Q VLAN Setting, 802.1Q Port Setting, Port Based VLAN

### 802.1Q VLAN Setting

VLAN Database:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Usage:

Use **vlan database** command to enter the VLAN configuration mode.

3. Command Syntax:

vlan database

4. Example:

The following example changes to VLAN configuration mode from Configure mode:

```
switch_a(config)#vlan database
switch_a(config-vlan)#
```

Add VLAN/Delete VLAN:

1. Command Mode: VLAN Configure mode

Logon to Configure Mode (Configure Terminal Mode).

Logon to VLAN Configure Mode.

The **switch\_a(config-vlan)#** prompt will show on the screen.

```
switch_a(config)#vlan database
switch_a(config-vlan)#
```

2. Usage:

This command enables or disables the state of a particular VLAN on a bridge basis. Specifying the disable state causes all forwarding over the specified VLAN ID on the specified bridge to cease. Specifying the enable state allows forwarding of frames on the specified VLAN-aware bridge.

3. Command Syntax:

vlan VLANID bridge GROUP name VLAN\_NAME state enable/disable

no vlan VLANID bridge GROUP

VLANID The VID of the VLAN that will be enabled or disabled on the bridge <2-4094>.

GROUP <1-1> The ID of the bridge-group on which the VLAN will be affected.

VLAN\_NAME The ASCII name of the VLAN. Maximum length: 16

characters.  
enable Sets VLAN into an enable state.  
disable Sets VLAN into a disable state.

#### 4. Example:

The following example enables the vlan VLANID (2) and name VLAN\_NAME (vlan2) of bridge GROUP (1):

```
switch_a(config-vlan)#vlan 2 bridge 1 name vlan2 state enable
switch_a(config-vlan)#
```

### 802.1Q Port Setting

Switchport mode access:

#### 1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

#### 2. Usage:

Use **switchport mode access** command to set the switching characteristics of the Layer-2 interface to access mode, and classify untagged frames only.

Use the **no switchport access** command to reset the mode of the Layer-2 interface to access (default).

#### 3. Command Syntax:

switchport mode access

no switchport access

#### 4. Example:

The following example sets the **switchport mode access** of the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#switchport mode access
switch_a(config-if)#
```

Switchport mode hybrid:

#### 1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

#### 2. Usage:

Use **switchport mode hybrid** command to set the switching characteristics of the Layer-2 interface as hybrid, and classify both tagged and untagged



frames.

Use the **no switchport hybrid** command to reset the mode of the Layer-2 interface to access (default).

3. Command Syntax:

switchport mode hybrid

switchport mode hybrid acceptable-frame-type all/vlan-tagged

no switchport hybrid

all Set all frames can be received.

vlan-tagged Set vlan-tagged frames can only be received.

4. Example:

The following example sets the **switchport mode hybrid** of the interface fe1 (port 1) and all frames to be received on interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#switchport mode hybrid acceptable-frame-type all
switch_a(config-if)#
```

Switchport mode trunk:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Usage:

Use **switchport mode trunk** command to set the switching characteristics of the Layer-2 interface as trunk, and specify only tagged frames.

Use the **no switchport trunk** command to reset the mode of the Layer-2 interface to access (default).

3. Command Syntax:

switchport mode trunk

no switchport trunk

4. Example:

The following example sets the **switchport mode trunk** of the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#switchport mode trunk
switch_a(config-if)#
```

Switchport hybrid allowed vlan:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

### 2. Usage:

Use this command to set the switching characteristics of the Layer-2 interface to hybrid. Both tagged and untagged frames will be classified over hybrid interfaces.

Use the no parameter to turn off allowed hybrid switching.

### 3. Command Syntax:

switchport hybrid allowed vlan all

switchport hybrid allowed vlan none

switchport hybrid allowed vlan add VLANID egress-tagged enable/disable

switchport hybrid allowed vlan remove VLANID

no switchport hybrid vlan

all Allow all VLANs to transmit and receive through the Layer-2 interface.

none Allow no VLANs to transmit and receive through the Layer-2 interface.

add Add a VLAN to the member set.

remove Remove a VLAN from the member set.

VLANID <2-4094> The ID of the VLAN or VLANs that will be added to, or removed from, the Layer-2 interface.

For a VLAN range, specify two VLAN numbers: lowest, then highest number in the range, separated by a hyphen.

For a VLAN list, specify the VLAN numbers separated by commas.

egress-tagged

enable Enable the egress tagging for the outgoing frames.

disable Disable the egress tagging for the outgoing frames.

### 4. Example:

The following example specifies to **add** the interface fe1 (port 1) to VLANID (2) and **enable** the **egress-tagged** for the outgoing frames on interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#switchport hybrid allowed vlan add 2 egress-tagged enable
switch_a(config-if)#
```

Switchport trunk allowed vlan:

#### 1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

### 2. Usage:

Use this command to set the switching characteristics of the Layer-2 interface to trunk. The all parameter indicates that any VLAN ID is part of its port's member set. The none parameter indicates that no VLAN ID is configured on

this port. The add and remove parameters will add and remove VLAN IDs to/from the port's member set.

Use the no parameter to remove all VLAN IDs configured on this port.

3. Command Syntax:

switchport trunk allowed vlan all

switchport trunk allowed vlan none

switchport trunk allowed vlan add VLANID

switchport trunk allowed vlan remove VLANID

switchport trunk allowed vlan except VLANID

no switchport trunk vlan

all Allow all VLANs to transmit and receive through the Layer-2 interface.

none Allow no VLANs to transmit and receive through the Layer-2 interface.

add Add a VLAN to transmit and receive through the Layer-2 interface.

remove Remove a VLAN from transmit and receive through the Layer-2 interface.

except All VLANs, except the VLAN for which the ID is specified, are part of its ports member set.

VLANID <2-4094> The ID of the VLAN or VLANs that will be added to, or removed from, the Layer-2 interface. A single VLAN, VLAN range, or VLAN list can be set.

For a VLAN range, specify two VLAN numbers: lowest, then highest number in the range, separated by a hyphen.

For a VLAN list, specify the VLAN numbers separated by commas.

4. Example:

The following example specifies to **add** the interface fe1 (port 1) to VLANID (2):

```
switch_a(config)#interface fe1
switch_a(config-if)#switchport trunk allowed vlan add 2
switch_a(config-if)#
```

### **Port Based VLAN**

Switchport portbase add/remove vlan:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Usage:

Use this command to set or remove the default VLAN for the interface.

3. Command Syntax:

switchport portbase add | remove vlan VLANID

VLANID The ID of the VLAN will be added to or removed from the Layer-2 interface.

4. Example:

The following example specifies to **add** the interface fe1 (port 1) to VLANID (2):

```
switch_a(config)#interface fe1
switch_a(config-if)#switchport portbase add vlan 2
switch_a(config-if)#
```

## QoS

Global Configuration, 802.1p Priority, DSCP

### Global Configuration

QoS:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **mls qos enable** command to globally enable QoS.

Use the **no mls qos** command to globally disable QoS.

3. Command Syntax:

mls qos enable

(no) mls qos

4. Example:

The following example globally enables QoS on the switch:

```
switch_a(config)#mls qos enable
switch_a(config)#
```

Trust:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **mls qos trust** command to turn on QoS trust CoS or DSCP.

Use the **no mls qos trust** command to turn off QoS trust CoS or DSCP.

3. Command Syntax:

(no) mls qos trust cos/dscp

cos Class of Service.

dscp Differentiated Service Code Point.

4. Example:

The following example turns on QoS trust CoS on the switch:

```
switch_a(config)#mls qos trust cos
switch_a(config)#
```

Strict Priority:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **priority-queue out** command to enable the egress expedite queue.

Use the **no priority-queue out** command to disable the egress expedite queue.

3. Command Syntax:

(no) priority-queue out

4. Example:

The following example enables the egress expedite queue on the switch:

```
switch_a(config)#priority-queue out
switch_a(config)#
```

Weighted Round Robin:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **wrr-queue bandwidth** command to specify the bandwidth ratios of the transmit queues.

3. Command Syntax:

wrr-queue bandwidth WRR\_WTS

WRR\_WTS Weighted Round Robin (WRR) weights for the 4 queues (4 values separated by spaces). Range is 1-55.

4. Example:

The following example specifies the bandwidth ratios of the transmit queues on the switch:

```
switch_a(config)#wrr-queue bandwidth 1 2 4 8
switch_a(config)#
```

### 802.1p Priority

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **wrr-queue cos-map** command to specify CoS values for a queue.

3. Command Syntax:

wrr-queue cos-map QUEUE\_ID COS\_VALUE

QUEUE\_ID Queue ID. Range is 0-3.

COS\_VALUE CoS values. Up to 8 values (separated by spaces). Range is 0-7.

4. Example:

The following example shows mapping CoS values 0 and 1 to queue 1 on the switch:

```
switch_a(config)#wrr-queue cos-map 1 0 1
switch_a(config)#
```

### **DSCP**

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **mls qos map dscp-queue** command to map the DSCP values to a queue.

3. Command Syntax:

**mls qos map dscp-queue** DSCP\_VALUE to QUEUE\_ID

DSCP\_VALUE DSCP values. Up to 8 values (separated by spaces). Range is 0-63.

QUEUE\_ID Queue ID. Range is 0-3.

4. Example:

The following example shows mapping DSCP values 0 to 3 to queue 1 on the switch:

```
switch_a(config)#mls qos map dscp-queue 0 1 2 3 to 1
switch_a(config)#
```

## SNMP

SNMP General Setting, SNMP v1/v2c, SNMP v3

### **SNMP General Setting**

SNMP Status:

1. Command Mode: Configure mode  
Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server enable** command to enable and **no snmp-server enable** command to disable SNMP to the switch.

3. Command Syntax:  
(no) snmp-server enable

4. Example:

The following example enables SNMP to the switch:

```
switch_a(config)#snmp-server enable  
switch_a(config)#
```

Description:

1. Command Mode: Configure mode  
Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server description** command to specify and **no snmp-server description** command to remove description for SNMP.

3. Command Syntax:  
snmp-server description DESCRIPTION  
no snmp-server description  
DESCRIPTION The description for SNMP.

4. Example:

The following example specifies description (**description**) for SNMP:

```
switch_a(config)#snmp-server description description  
switch_a(config)#
```

Location:

1. Command Mode: Configure mode  
Logon to Configure Mode (Configure Terminal Mode).



The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server location** command to specify and **no snmp-server location** command to remove location for SNMP.

3. Command Syntax:

snmp-server location LOCATION

no snmp-server location

LOCATION The location for SNMP.

4. Example:

The following example specifies location (**location**) for SNMP:

```
switch_a(config)#snmp-server location location
switch_a(config)#
```

Contact:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server contact** command to specify and **no snmp-server contact** command to remove contact for SNMP.

3. Command Syntax:

snmp-server contact CONTACT

no snmp-server contact

CONTACT The contact for SNMP.

4. Example:

The following example specifies contact (**contact**) for SNMP:

```
switch_a(config)#snmp-server contact contact
switch_a(config)#
```

Trap Community Name:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to specify trap community name for SNMP.

Use the no parameter with this command to remove trap community name for SNMP.

3. Command Syntax:

snmp-server trap-community <1-5> NAME  
no snmp-server trap-community <1-5>  
<1-5> The trap community 1-5.  
NAME The trap community name for SNMP.

4. Example:

The following example specifies trap community name 1 (**name**) for SNMP:

```
switch_a(config)#snmp-server trap-community 1 name
switch_a(config)#
```

Trap Host IP Address:

1. Command Mode: Configure mode

Login to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to specify trap host IP address for SNMP.

Use the no parameter with this command to remove trap host IP address for SNMP.

3. Command Syntax:

snmp-server trap-ipaddress <1-5> IP-ADDRESS

no snmp-server trap-ipaddress <1-5>

<1-5> The trap host IP address 1-5.

IP-ADDRESS The trap host IP address for SNMP. A.B.C.D specifies the IP address.

4. Example:

The following example specifies trap host 1 IP address (**169.254.1.2**) for SNMP:

```
switch_a(config)#snmp-server trap-ipaddress 169.254.1.2
switch_a(config)#
```

Cold Start Trap:

1. Command Mode: Configure mode

Login to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server trap-type enable coldStart** command to enable cold start trap for SNMP.

Use the **no snmp-server trap-type enable coldStart** command to disable cold start trap for SNMP.

3. Command Syntax:

(no) snmp-server trap-type enable coldStart

4. Example:

The following example enables cold start trap for SNMP:

```
switch_a(config)#snmp-server trap-type enable coldStart
switch_a(config)#
```

Warm Start Trap:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server trap-type enable warmStart** command to enable warm start trap for SNMP.

Use the **no snmp-server trap-type enable warmStart** command to disable warm start trap for SNMP.

3. Command Syntax:

(no) snmp-server trap-type enable warmStart

4. Example:

The following example enables warm start trap for SNMP:

```
switch_a(config)#snmp-server trap-type enable warmStart
switch_a(config)#
```

Link Down Trap:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server trap-type enable linkDown** command to enable link down trap for SNMP.

Use the **no snmp-server trap-type enable linkDown** command to disable link down trap for SNMP.

3. Command Syntax:

(no) snmp-server trap-type enable linkDown

4. Example:

The following example enables link down trap for SNMP:

```
switch_a(config)#snmp-server trap-type enable linkDown
switch_a(config)#
```

Link Up Trap:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server trap-type enable linkUp** command to enable link up trap for SNMP.

Use the **no snmp-server trap-type enable linkUp** command to disable link up trap for SNMP.

3. Command Syntax:

(no) snmp-server trap-type enable linkUp

4. Example:

The following example enables link up trap for SNMP:

```
switch_a(config)#snmp-server trap-type enable linkUp
switch_a(config)#
```

Authentication Failure Trap:

1. Command Mode: Configure mode

Login to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server trap-type enable authenticationFailure** command to enable authentication failure trap for SNMP.

Use the **no snmp-server trap-type enable authenticationFailure** command to disable authentication failure trap for SNMP.

3. Command Syntax:

(no) snmp-server trap-type enable authenticationFailure

4. Example:

The following example enables authentication failure trap for SNMP:

```
switch_a(config)#snmp-server trap-type enable authenticationFailure
switch_a(config)#
```

Topology Change Trap:

1. Command Mode: Configure mode

Login to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server trap-type enable topologyChange** command to enable topology change trap for SNMP.

Use the **no snmp-server trap-type enable topologyChange** command to disable topology change trap for SNMP.

3. Command Syntax:

(no) snmp-server trap-type enable topologyChange

4. Example:

The following example enables topology change trap for SNMP:

```
switch_a(config)#snmp-server trap-type enable topologyChange
switch_a(config)#
```

### **SNMP v1/v2c**

Get Community Name:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server community get** command to specify and **no snmp-server community get** command to remove get community name for SNMP.

3. Command Syntax:

snmp-server community get NAME

no snmp-server community get

NAME The get community name for SNMP.

4. Example:

The following example specifies get community name (**name**) for SNMP:

```
switch_a(config)#snmp-server community get name
switch_a(config)#
```

Set Community Name:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **snmp-server community set** command to specify and **no snmp-server community set** command to remove get community name for SNMP.

3. Command Syntax:

snmp-server community set NAME

no snmp-server community set

NAME The set community name for SNMP.

4. Example:

The following example specifies set community name (**name**) for SNMP:

```
switch_a(config)#snmp-server community set name
switch_a(config)#
```

### SNMP v3

SNMPv3 No-Auth:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Add a user using snmp v3 with read-only or read-write access mode and without authentication. Use the no form of the command to delete this user.

3. Command Syntax:

(no) snmp-server v3-user USERNAME (ro | rw) noauth

USERNAME Specify a user name.

ro read-only access mode

rw read-write access mode

4. Example:

The following example adds a user (**myuser**) using snmp v3 with read-only access mode and without authentication:

```
switch_a(config)#snmp-server v3-user myuser ro noauth
switch_a(config)#
```

SNMPv3 Auth-MD5, SNMPv3 Auth-SHA:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Add a user using snmp v3 with read-only or read-write access mode and with MD5 or SHA authentication. Use the no form of the command to delete this user.

3. Command Syntax:

(no) snmp-server v3-user USERNAME (ro | rw) auth (md5 | sha)

AUTH\_PASSWORD

USERNAME Specify a user name.

ro read-only access mode

rw read-write access mode

md5 authentication method

sha authentication method

AUTH\_PASSWORD authentication password

4. Example:

The following example adds a user (**myuser**) using snmp v3 with read-write access mode and MD5 authentication (**mypassword**):

```
switch_a(config)#snmp-server v3-user myuser rw auth md5 mypassword
```

```
switch_a(config)#
```

SNMPv3 Priv Auth-MD5, SNMPv3 Priv Auth-SHA:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Add a user using snmp v3 with read-only or read-write access mode, MD5 or SHA authentication, and privacy. Use the no form of the command to delete this user.

3. Command Syntax:

(no) snmp-server v3-user USERNAME (ro | rw) priv auth (md5 | sha)

AUTH\_PASSWORD des PRIV\_PASS\_PHRASE

USERNAME Specify a user name.

ro read-only access mode

rw read-write access mode

md5 authentication method

sha authentication method

AUTH\_PASSWORD authentication password

PRIV\_PASS\_PHRASE encryption pass phrase

4. Example:

The following example adds a user (**myuser**) using snmp v3 with read-write access mode, MD5 authentication (**mypassword**), and encryption pass phrase (**mypassphrase**):

```
switch_a(config)#snmp-server v3-user myuser rw priv md5 mypassword  
des mypassphrase  
switch_a(config)#
```

## Other Protocols

GVRP, IGMP Snooping

### GVRP

GVRP:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **set gvrp enable bridge** command to enable (set) and **set gvrp disable bridge** command to disable (reset) GVRP globally for the bridge instance. This command does not enable/disable GVRP in all ports of the bridge. After enabling GVRP globally, use the **set port gvrp enable** command to enable GVRP on individual ports of the bridge.

3. Command Syntax:

set gvrp enable bridge GROUP

set gvrp disable bridge GROUP

GROUP Bridge-group ID used for bridging.

4. Example:

The following example globally enables GVRP to bridge GROUP (1):

```
switch_a(config)#set gvrp enable bridge 1
switch_a(config)#
```

Dynamic VLAN creation:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **set gvrp dynamic-vlan-creation enable bridge** command to enable and **set gvrp dynamic-vlan-creation disable bridge** command to disable dynamic VLAN creation for a specific bridge instance.

3. Command Syntax:

set gvrp dynamic-vlan-creation enable bridge GROUP

set gvrp dynamic-vlan-creation disable bridge GROUP

GROUP Bridge-group ID used for bridging.

4. Example:

The following example enables dynamic VLAN creation for bridge GROUP



(1):

```
switch_a(config)#set gvrp dynamic-vlan-creation enable bridge 1
switch_a(config)#
```

Per port setting:

GVRP:

1. Command Mode: Configure mode

Login to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use **set port gvrp enable** command to enable and **set port gvrp disable** command to disable GVRP on a port or all ports in a bridge.

3. Command Syntax:

set port gvrp enable all/IFNAME

set port gvrp disable all/IFNAME

all All ports added to recently configured bridge.

IFNAME The name of the interface.

4. Example:

The following example enables GVRP on the interface fe1 (port 1):

```
switch_a(config)#set port gvrp enable fe1
switch_a(config)#
```

Per port setting:

GVRP applicant:

1. Command Mode: Configure mode

Login to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to set the GVRP applicant state to normal or active.

3. Command Syntax:

set gvrp applicant state active/normal IFNAME

active Active state

normal Normal state

IFNAME Name of the interface.

4. Example:

The following example sets GVRP applicant state to active on the interface fe1 (port 1):

```
switch_a(config)#set gvrp applicant state active fe1
switch_a(config)#
```

Per port setting:

GVRP registration:

1. Command Mode: Configure mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

```
switch_a(config)#
```

2. Command:

Use this command to set GVRP registration to normal, fixed, and forbidden registration mode for a given port.

3. Command Syntax:

set gvrp registration normal IF\_NAME

set gvrp registration fixed IF\_NAME

set gvrp registration forbidden IF\_NAME

normal Specify dynamic GVRP multicast registration and deregistration on the port.

fixed Specify the multicast groups currently registered on the switch are applied to the port, but any subsequent registrations or deregistrations do not affect the port. Any registered multicast groups on the port are not deregistered based on the GARP timers.

forbidden Specify that all GVRP multicasts are deregistered, and prevent any further GVRP multicast registration on the port.

IF\_NAME The name of the interface.

4. Example:

The following example sets GVRP registration to fixed registration mode on the interface fe1 (port 1):

```
switch_a(config)#set gvrp registration fixed fe1
switch_a(config)#
```

### **IGMP Snooping**

IGMP mode:

Querier:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

vlan1.1 means vlan 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface vlan1.1
switch_a(config-if)#
```

2. Command:

Use **ip igmp snooping querier** command to enable IGMP querier operation on a subnet (VLAN) when no multicast routing protocol is configured in the subnet (VLAN). When enabled, the IGMP Snooping querier sends out periodic IGMP queries for all interfaces on that VLAN.

Use the **no ip igmp snooping querier** command to disable IGMP querier configuration.

3. Command Syntax:  
(no) ip igmp snooping querier

4. Example:

The following example enables IGMP snooping querier on **vlan1.1**:

```
switch_a(config)#interface vlan1.1
switch_a(config-if)#ip igmp snooping querier
```

IGMP mode:

Passive:

1. Command Mode: Configure mode or Interface mode

Logon to Configure Mode (Configure Terminal Mode).

The **switch\_a(config)#** prompt will show on the screen.

Then logon to Interface mode.

vlan1.1 means vlan 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a#configure terminal
switch_a(config)#
```

```
switch_a(config)#interface vlan1.1
switch_a(config-if)#
```

2. Command:

Use **ip igmp snooping** command to enable IGMP Snooping. When this command is given in the Global Config mode, IGMP Snooping is enabled at the switch level. When this command is given at the VLAN interface level, IGMP Snooping is enabled for that VLAN.

Use the **no ip igmp snooping** command to globally disable IGMP Snooping, or for the specified interface.

3. Command Syntax:  
(no) ip igmp snooping

4. Example:

The following example enables IGMP snooping on the switch or **vlan1.1**:

```
switch_a#configure terminal
switch_a(config)# ip igmp snooping
switch_a(config)#interface vlan1.1
switch_a(config-if)#ip igmp snooping
```

IGMP version:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **ip igmp version** command to set the current IGMP protocol version on an interface.

To return to the default version, use the **no ip igmp version** command.

3. Command Syntax:

ip igmp version VERSION

no ip igmp version

VERSION IGMP protocol version number.

4. Example:

The following example sets the IGMP protocol version 3 on the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#ip igmp version 3
```

Fast-leave:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

vlan1.1 means vlan 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface vlan1.1
switch_a(config-if)#
```

2. Command:

Use **ip igmp snooping fast-leave** command to enable IGMP Snooping fast-leave processing. Fast-leave processing is analogous to immediate leave processing; the IGMP group-membership is removed, as soon as an IGMP leave group message is received without sending out a group-specific query.

Use the **no ip igmp snooping fast-leave** command to disable fast-leave processing.

3. Command Syntax:

(no) ip igmp snooping fast-leave

4. Example:

The following example enables IGMP snooping fast-leave on **vlan1.1**:

```
switch_a(config)#interface vlan1.1
switch_a(config-if)#ip igmp snooping fast-leave
```

IGMP querier:

Query-interval:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **ip igmp query-interval** command to configure the frequency of sending IGMP host query messages.

To return to the default frequency, use the **no ip igmp query-interval** command.

3. Command Syntax:

**ip igmp query-interval** INTERVAL

**no ip igmp query-interval**

INTERVAL <1-18000> Frequency (in seconds) at which IGMP host query messages are sent.

4. Example:

The following example changes the frequency of sending IGMP host-query messages to 2 minutes on the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#ip igmp query-interval 120
```

IGMP querier:

Max-response-time:

1. Command Mode: Interface mode

Logon to Configure Mode (Configure Terminal Mode).

Then logon to Interface mode.

fe1 means port 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface fe1
switch_a(config-if)#
```

2. Command:

Use **ip igmp query-max-response-time** command to configure the frequency of sending IGMP host query messages.

To return to the default frequency, use the **no ip igmp query-max-response-time** command.

3. Command Syntax:

**ip igmp query-max-response-time** RESPONSETIME

**no ip igmp query-max-response-time**

RESPONSETIME <1-240> Maximum response time (in seconds) advertised in IGMP queries.

4. Example:

The following example configures a maximum response time of 8 seconds on the interface fe1 (port 1):

```
switch_a(config)#interface fe1
switch_a(config-if)#ip igmp query-max-response-time 8
```

IGMP passive snooping:

Static mc router port:

1. Command Mode: Interface mode  
Logon to Configure Mode (Configure Terminal Mode).  
Then logon to Interface mode.

vlan1.1 means vlan 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface vlan1.1
switch_a(config-if)#
```

2. Command:

Use **ip igmp snooping mrouter interface** command to statically configure the specified VLAN constituent interface as a multicast router interface for IGMP Snooping in that VLAN.

Use the **no ip igmp snooping mrouter interface** command to remove the static configuration of the interface as a multicast router interface.

3. Command Syntax:

(no) ip igmp snooping mrouter interface IFNAME  
IFNAME Specify the name of the interface

4. Example:

The following example shows interface fe1 (port 1) statically configured to be a multicast router interface on **vlan1.1**:

```
switch_a(config)#interface vlan1.1
switch_a(config-if)#ip igmp snooping mrouter interface fe1
```

IGMP passive snooping:

Report suppression:

1. Command Mode: Interface mode  
Logon to Configure Mode (Configure Terminal Mode).  
Then logon to Interface mode.

vlan1.1 means vlan 1.

The **switch\_a(config-if)#** prompt will show on the screen.

```
switch_a(config)#interface vlan1.1
switch_a(config-if)#
```

2. Command:

Use **ip igmp snooping report-suppression** command to enable report suppression for IGMP versions 1 and 2.

Use the **no ip igmp snooping report-suppression** command to disable report suppression.

3. Command Syntax:

(no) ip igmp snooping report-suppression

4. Example:

The following example enables report suppression for IGMPv2 reports on **vlan1.1**:

```
switch_a(config)#interface vlan1.1  
switch_a(config-if)#ip igmp version 2  
switch_a(config-if)#ip igmp snooping report-suppression
```

## Specifications

<b>Applicable Standards</b>	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3ab 1000BaseT IEEE 802.3z 1000BaseSX
<b>Switching Method</b>	Store-and-Forward
<b>Forwarding Rate</b>	
10BaseT	10 / 20Mbps half / full-duplex
100BaseTX	100 / 200Mbps half / full-duplex
1000BaseT	2000Mbps full-duplex
1000BaseSX	2000Mbps full-duplex
<b>Performance</b>	14,880pps for 10Mbps 148,810pps for 100Mbps 1,488,100pps for 1000Mbps
<b>Cable</b>	
10BaseT	2-pair UTP/STP Cat. 3, 4, 5 Up to 100m (328ft)
100BaseTX	2-pair UTP/STP Cat. 5 Up to 100m (328ft)
1000BaseT	4-pair UTP/STP Cat. 5 Up to 100m (328ft)
1000BaseSX	50 or 62.5/125µm multi-mode fiber (850nm) up to 550m
<b>LED Indicators</b>	Per unit – Power status (Power 1, 2, 3) Per port – Link/ACT and 10/100 or 1000 Mbps
<b>Dimensions</b>	235mm (W) * 125mm(D) * 50mm( H)
<b>Net Weight</b>	1.5kg approx.
<b>Power Input</b>	Terminal Block: 24VDC
<b>Power Consumption</b>	15W max.
<b>Operating Temperature</b>	-40°C to 75°C (-40°F to 167°F) Tested for functional operation @ -40°C to 85°C (-40°F to 185°F)
<b>Storage Temperature</b>	-40°C to 85°C (-40°F to 185°F)
<b>Humidity</b>	5%-95% non-condensing
<b>Safety</b>	UL508, EN60950-1, IEC60950-1
<b>EMI</b>	FCC Part 15, Class B EN61000-6-3: EN55022, EN61000-3-2, EN61000-3-3
<b>EMS</b>	EN61000-4-2 (ESD Standard) EN61000-4-3 (Radiated RFI Standards) EN61000-4-4 (Burst Standards) EN61000-4-5 (Surge Standards) EN61000-4-6 (Induced RFI Standards) EN61000-4-8 (Magnetic Field Standards) EN61000-4-11 (Voltage Dips Standards)



<b>Environmental Test Compliance</b>	IEC60068-2-6 Fc (Vibration Resistance)
	IEC60068-2-27 Ea (Shock)
	IEC60068-2-32 Ed (Free Fall)
NEMA TS1/2 Environmental requirements for traffic control equipment	

## Appendix

### B9 DCE pin assignment

Pin no.	Name	RS232 Signal name
1	DCD	Data Carrier detect
2	RxD	Received data
3	TxD	Transmit data
4	---	N/C
5	GND	Signal ground
6	DSR	Data set Ready
7	---	N/C
8	CTS	Clear to send
9	---	N/C